

## **Specification Sheet**

Part Number: 181-24011



Slotted Wall Wiring Duct, 2" x 4", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	181-24011
Туре	SL2X4
Color	White (WH)
Features & Benefits	<ul> <li>Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> <li>Restricted opening design in the finger of the duct helps keep wires in place.</li> <li>Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection. Supplied with mounting holes to streamline installation.</li> <li>Optional covers enhance protection and appearance.</li> </ul>
Quantity Per	carton

Product Description	additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and Ts.
Short Description	Slotted Wall Wiring Duct, 2" x 4", Non-Adhesive, PVC, White, 120ft/Carton
Global Part Name	SL2X4-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	2.0
Width W (Metric)	50.8
Height H (Imperial)	4.07
Height H (Metric)	103.4
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC

Self-Extinguishing

Pro-Duct slotted wall wiring duct features break-away fingers which provide

**Product Description** 

Flammability

Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	UL CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013
UL Recognized (US)	Yes
Package Quantity(Imperial)	120
Package Quantity (Metric)	36.58
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

<sup>© 2019</sup> HellermannTyton. All Rights Reserved.