


C062C822K2G5CA

Aliases (C062C822K2G5CA)

LDD Comm COG, Ceramic, 8200 pF, 10%, 200 VDC, COG, Lead Spacing = 5.08mm



Click here for the 3D model.

| Dimensions | |
|------------|-------------------------|
| L | 7.37mm +/-0.25mm |
| Н | 7.37mm +/-0.25mm |
| Т | 2.29mm +/-0.25mm |
| S | 5.08mm +/-0.38mm |
| LL | 31.75mm MIN |
| F | 0.635mm +0.102/-0.051mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 100 |

| General Information | | |
|---------------------|---|--|
| Series | LDD Comm COG | |
| Style | Radial | |
| Features | Commercial | |
| RoHS | No | |
| Prop 65 | A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov. | |
| SCIP Number | 8c864fd1-202b-4ce7-85fd-56c9e19121ad | |
| Termination | Lead (SnPb) | |
| Failure Rate | N/A | |
| AEC-Q200 | No | |

| Specifications | | | |
|---------------------------------|----------------|--|--|
| Capacitance | 8200 pF | | |
| Capacitance Tolerance | 10% | | |
| Voltage DC | 200 VDC | | |
| Dielectric Withstanding Voltage | 500 VDC | | |
| Temperature Range | -55/+125°C | | |
| Temperature Coefficient | COG | | |
| Dissipation Factor | 0.1% 1 kHz 25C | | |
| Insulation Resistance | 122 MOhms | | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.