

Page 1 of 6 SDS-E-CL-ETCH-16

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, EU & GHS Standards SDS Revision Date: 12/9/2020 SDS Revision: 4.0 1. PRODUCT & COMPANY IDENTIFICATION 1.1 Product Name: PCB ETCHANT SOLUTION, (P/N CL-ETCH-16), 16 oz./473 mL 1.2 Chemical Name: 1.3 Synonyms: CL-ETCH-16 Trade Names: 1.4 PCB Etchant Solution, (P/N CL-ETCH-16) Product Uses & Restrictions: 1.5 **Etchant Solution** 16 Distributor's Name: CAIG Laboratories, Inc. 17 Distributor's Address: 12200 Thatcher Court, Poway, CA 92064-6876 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN205206) Business Phone / Fax: 19 +1 (800) 224-4123 2. HAZARDS IDENTIFICATION 2.1 Hazard Identification: Prepared in accordance with UN Globally Harmonized standards. Intended to comply with OSHA 29 CFR 1910.1200, Canadian WHMIS and Australian Work Health and Safety standards. This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of WHSR and ADG Code (Australia). WARNING! MAY BE CORROSIVE TO METALS. HARMFUL IF SWALLOWED. CAUSES SERIOUS EYE DAMAGE. MAY CAUSE RESPIRATORY IRRITATION. Classification: Met. Corr. 1; Acute Tox. 4; Eye Dam. 1; STOT SE 3 2.2 Label Flements: Hazard Statements (H): H290 - May be corrosive to metals. H302 - Harmful if swallowed. H318 -Causes serious eye damage. H335 – May cause respiratory irritation. Precautionary Statements (P): P234 - Keep only in original packaging. P261 - Avoid breathing dust/ vapors. P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear eye protection/face protection. P301+P312 – IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 - Rinse mouth. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 immediately call a POINSON CENTER doctor. P390 - Absorb spillage to prevent materialdamage. P406 - Store in a corrosion resistant container with a resistant inner liner. P403+P233 -Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P501 -Dispose of contents/container through licensed treatment, storage, or disposal facility Other Warnings: In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. KEEP OUT OF REACH OF CHILDREN. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-TLV CHEMICAL NAME(S) CAS No. RTECS No. **EINECS No.** STEL **TWA** STEL **PEAK** PEL STEL **IDLH** OTHER 7732-18-5 ZC0110000 231-191-2 40-70 NA NA NF NF NF NA NA NA WATER (AQUA) LJ9100000 231-729-4 30-60 NA 7705-08-0 1 1 NF NF NF NA NA Fe SOLID FERRIC CHLORIDE Met. Corr. 1; Acute Tox. 4; Skin Irrit. 2; Eye Dam. 1; H290, H302, H315, H318 NO5400000 NF NA Fe SOLID 7758-94-3 231-843-4 NA 1 1 NF NF NA NA FERROUS CHLORIDE Met. Corr. 1; Acute Tox. 4; Eye Dam. 1; H290, H302, H318 7647-01-0 MW4025000 231-595-7 0.1-1.0 2 5 5 7.5 5 5 7 50 HYDROCHLORIC ACID Skin Corr. 1B, STOT SE 3; H314, H335 4. FIRST AID MEASURES First Aid: As a precaution remove contact lenses if worn and flush eyes thoroughly with copious amounts of water Eyes: for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If irritation persists, seek immediate medical attention Remove contaminated clothing. Use a waterless hand cleaner, mineral oil, or petroleum jelly to remove the Skin: material. Then wash the skin with soap and water If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. Do not induce vomiting unless directed to by a physician. Do not give anything to drink unless directed to Ingestion: by a physician. Never give anything by mouth to a person who is not fully conscious. Seek medical attention immediately. Inhalation: Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product immediately remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.



Page 2 of 6 SDS-E-CL-ETCH-16

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, EU & GHS Standards SDS Revision Date: 12/9/2020 SDS Revision: 4.0 4. FIRST AID MEASURES - cont'd 4.2 Effects of Exposure: This product can cause transient eye irritation and discomfort, tearing and blurred vision with short-term Eyes: contact with liquid sprays or mists. Skin: This product can cause transient skin irritation with short-term exposure. If swallowed, may lead to vomiting, reduced appetite abdominal pain, lethargy, tar like stools, diarrhea, fast Ingestion: and weak pulse, hypertension, dehydration, acidosis, and coma. Inhalation: Severe respiratory irritation (from vapors or mists) is possible. Inhalation of fumes can cause upper respiratory tract and lung irritation. Aspiration of liquid into the lungs can cause lung damage. 4.3 Symptoms of Overexposure: Eye irritation and discomfort, tearing and blurred vision. Eyes: Transient skin irritation with short-term exposure. Can cause serious skin damage with repeated Skin: exposure. Ingestion: If swallowed, may lead to vomiting, reduced appetite abdominal pain, lethargy, tar like stools, diarrhea, fast and weak pulse, hypertension, dehydration, acidosis, and coma. Inhalation: Severe respiratory irritation (from vapors or mists) is possible. Inhalation of fumes can cause upper respiratory tract and lung irritation. Aspiration of liquid into the lungs can cause lung damage. 4.4 Acute Health Effects: Possible discoloration of the eye tissues, eye irritation and discomfort, tearing and blurred vision. Eye Eyes: corrosion with corneal or conjunctival ulceration. Prolonged skin contact may cause skin burns or ulceration. Ferric chloride has been infrequently Skin: associated with skin sensitization in humans. Indestion higher doses may lead to abnormal liver function with nausea and vomiting, reduced appetite Ingestion: abdominal pain, lethargy, tarry stools, diarrhea, fast and weak pulse, hypertension, dehydration, acidosis, and coma. Temporary alteration of the heart's electrical activity may result in irregular pulse palpations or inadequate circulation. If death does not occur immediately, symptoms may clear in a few hours but return within a day with cyanosis, pulmonary edema, shock, convulsions, acidosis, fever and death. Severe respiratory irritation (from vapors or mists) is possible. Inhalation of fumes can cause upper Inhalation: respiratory tract and lung irritation. At elevated temperatures or through mechanical action, may form vapors, mist or fumes that may be irritation to the eyes, nose, throat and lungs. Chronic Health Effects: 4.5 Abnormal liver function with nausea and vomiting, reduced appetite abdominal pain, lethargy, tarry stools, diarrhea, fast and weak pulse, hypertension, dehydration, acidosis, and coma. Temporary alteration of the heart's electrical activity may result in irregular pulse palpations or inadequate circulation. If death does not occur immediately, symptoms may clear in a few hours but return within a day with cyanosis, pulmonary edema, shock, convulsions, acidosis, fever and Target Organs: 46 Eyes, Skin, Liver, Respiratory System. 4.7 Medical Conditions Pre-existing diseases of the liver may have increased susceptibility to HEALTH Aggravated by Exposure: the toxicity of repeated exposures. **FLAMMABILITY** 0 PHYSICAL HAZARDS 2 PROTECTIVE EQUIPMENT X **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: Not considered to be a fire or explosion hazard. Will react with water to product toxic and corrosive fumes Extinguishing Methods: 5.2 Dry chemical, foam carbon dioxide and water fog. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective 6.1 Equipment. For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. U.S. EPA regulations require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll-free number for the US Coast Guard's National Response Center is +1 (800) 424-8802.



Page 3 of 6 SDS-E-CL-ETCH-16

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, EU & GHS Standards SDS Revision Date: 12/9/2020 SDS Revision: 4.0 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: 7.1 Do not eat, drink or smoke when handling this product. Wash hands thoroughly after using this product and before eating, drinking or smoking. Remove soiled clothing to prevent prolonged skin contact. Avoid breathing vapors. Avoid direct skin contact. 7.2 Storage & Handling: Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product Special Precautions: 7.3 Clean all spills promptly. Empty containers may contain product residues. Do not reuse empty containers without commercial cleaning or reconditioning 8. EXPOSURE CONTROLS & PERSONAL PROTECTION ACGIH NOHSC Exposure Limits: OTHER 8 1 ppm (mg/m3) CHEMICAL NAME(S) TLV STEL ES-TWA FS-STFI ES-PEAK PFI STFI IDLH FERRIC CHLORIDE 1 NF NF NF NA NA NA Fe SOLID FERROUS CHLORIDE NΑ NF NF NF Fe SOLID 1 1 NA NA HYDROCHLORIC ACID 8.2 Ventilation & Engineering A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Controls: Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details. 8.3 Respiratory Protection: If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerin, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face piece positivepressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. 8 4 Eve Protection: Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear googles and/or face shield if splashing or spraying is anticipated. Wear googles and face shield if material is heated above 125 °F (51 °C). Have suitable eye wash water available. 8.5 Hand Protection Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. Use heat-protective gloves when handling product at elevated temperatures. 86 Body Protection: Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Yellow brown deliquescent crystals 9.2 Odor Slight odor of hydrochloric acid. 9.3 Odor Threshold NA 9.4 pH: NA 9.5 Melting Point/Freezing Point: > 37 °C (> 99 °F) Initial Boiling Point/Boiling 9.6 NA Range: 9.7 Flashpoint NA 9.8 Upper/Lower Flammability NA 9.9 Vapor Pressure: 1.1 @ 194 °C (381 °F) Vapor Density 9.10 NA 9.11 Relative Density 2.9 g/cm3 @ 25 °C 9.12 Solubility Soluble in water 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA 9 16 Viscosity: NA Other Information: 9.17 NA



Page 4 of 6 SDS-E-CL-ETCH-16

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, EU & GHS Standards SDS Revision Date: 12/9/2020 SDS Revision: 4.0 10. STABILITY & REACTIVITY 10.1 Stability: Stable under normal conditions. 10.2 Hazardous Decomposition Emits toxic fumes of chloride when heated to decomposition. Products: Hazardous Polymerization: 10.3 Will not occur 10.4 Conditions to Avoid: Open flames, sparks, high heat, incompatible substances and direct sunlight. 10.5 Incompatible Substances: Metals, ally chloride, sodium potassium. Will react with water to product toxic and corrosive fumes. 11. TOXICOLOGICAL INFORMATION Ingestion: YES 11.1 Routes of Entry: Inhalation: YES Absorption: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product. Ferric Chloride: LD<sub>50</sub> (oral, Rat): 316 mg/kg; Hydrochloric Acid: LD<sub>50</sub> (oral, rabbit): 900 mg/kg 11.3 Acute Toxicity: See Section 4.4 Chronic Toxicity: 11.4 See Section 4.5 11.5 Suspected Carcinogen: NA Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans Mutagenicity: Investigated as a mutagen, reproductive effector. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 4.3 11.8 Biological Exposure Indices NE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: There are no specific data available for this product. 12.1 Effects on Plants & Animals: 12.2 There are no specific data available for this product 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 24-hour LC50: 6 mg/L (striped bass fingerling); 24-hour LC50: 4 mg/L (striped bass larvae) 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements 13.2 Special Considerations: NΑ 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): CONSUMER COMMODITY, ORM-D (IP VOL ≤ 5.0 L) - until 12/31/2013 14.1 UN2582, FERRIC CHLORIDE SOLUTION, 8, III, LTD QTY (IP VOL ≤ 5.0 L) UN2582, FERRIC CHLORIDE SOLUTION, 8, III (> 5.0 L) IATA (AIR): 14.2 UN2582, FERRIC CHLORIDE SOLUTION, 8, III (LTD QTY IP VOL ≤ 0.5 L) UN2582, FERRIC CHLORIDE SOLUTION, 8, III (IP > 0.5 L) 14.3 IMDG (OCN): UN2582, FERRIC CHLORIDE SOLUTION, 8, III, LTD QTY (IP VOL ≤ 5.0 L) UN2582, FERRIC CHLORIDE SOLUTION, 8, III (> 5.0 L) 14 4 TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 5.0 L) UN2582, FERRIC CHLORIDE SOLUTION, 8, III (> 5.0 L) 14.5 ADR/RID (EU): UN2582, FERRIC CHLORIDE SOLUTION, 8, III, LTD QTY (IP VOL ≤ 5.0 L) 14.6 SCT (MEXICO): UN2582, FERRIC CHLORIDE SOLUTION, 8, II, CANTIDAD LIMITADA (IP VOL ≤ 5.0 L) ADGR (AUS): UN2582, FERRIC CHLORIDE SOLUTION, 8, III, LTD QTY (IP VOL ≤ 5.0 L

### Page 5 of 6

# **SAFETY DATA SHEET**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 12/9/2020

riep	aieu iu Oona, ACC, AN	I, NOHSC, WHMIS, GHS & 12/2/2008/EC Standards   SDS Revision: 1.0   SDS Revision Date: 12/9/2020							
		15. REGULATORY INFORMATION							
15.1	SARA Reporting								
15.2	Requirements: SARA Threshold Planning	This product contains <u>Hydrochloric Acid</u> , a substance subject to SARA Title III, Section 313 reporting requirements.							
	Quantity:	Hydrochloric Acid: 2,270 kg (5,000 lbs).  The components of this product are listed on the TSCA Inventory.							
15.3 15.4	TSCA Inventory Status:  CERCLA Reportable Quantity	The components of this product are listed on the TSCA Inventory.							
	(RQ):	Hydrochloric Acid: 2,270 kg (5,000 lbs); Ferric Chloride: 1000 lb (454 kg)							
15.5	Other Federal Requirements:    Ferric Chloride (as Fe Solid) and Hydrochloric Acid are listed as a hazardous air pollutant (HAP). This material does not contain any Class 1 Ozone depleters. This material does not contain any Class 2 Ozone depleters. Ferric Chloride,   Ferrous Chloride and Hydrochloric Acid are listed as a Hazardous Substance under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. OSHA considers hydrochloric acid extremely hazardous.								
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class E, D2A							
15.7									
15.8	Other Requirements:	Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII. Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.  This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .							
		16. OTHER INFORMATION							
16.1	Other Information:	WARNING! MAY BE CORROSIVE TO METALS. HARMFUL IF SWALLOWED. CAUSES SERIOUS EYE DAMAGE MAY CAUSE RESPIRATORY IRRITATION. Keep only in original packaging. Avoid breathing dust/ vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POINSON CENTER doctor. Absorb spillage to prevent material-damage. Store in a corrosion resistant container with a resistant inner liner. Store in a well-ventilated place. Keep container tightly closed. Store locked up.  KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.							
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.							
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.							
16.4	Prepared for:	CAIG Laboratories, Inc.  12200 Thatcher Court  Poway, CA 92064-6876  Tel: +1 (800) CAIG-123 (244-4123)  Fax: +1 (858) 486-8398 fax  http://www.caig.com/							
16.5	Prepared by:	ShipMate, Inc.  P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com							

#### Page 6 of 6

## **SAFETY DATA SHEET**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 12/9/2020

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	CAS No. Chemical Abstract Service Number					
RTECS No. Registry of Toxic Effects of Chemical Substances Number						
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number					

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
IDLH	Immediately Dangerous to Life and Health			
NOHSC	National Occupational Health and Safety Commission (Australia)			
OSHA U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit				
STEL Short Term Exposure Limit				
TLV Threshold Limit Value				
TWA	Time Weighted Average			

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard			
1	1 Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			



#### PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D		H.	
Е			
F		H.	





#### OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic		
Irrit	Irritant		
NA	Not Available		
NR	No Results		
ND	Not Determined		
NE Not Established			
NF	Not Found		
SCBA	Self-Contained Breathing Apparatus		
Sens	Sensitization		
STOT RE   Specific Target Organ Toxicity – Repeat Exposure			
STOT SE	Specific Target Organ Toxicity – Single Exposure		

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

#### **HAZARD RATINGS:**

0	Minimal Hazard	FLAMMABILITY
1	Slight Hazard	\
2 Moderate Hazard		REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	── / <b>▼ ₩</b> У
₩	Use No Water	HEALTH 🔪
OX	Oxidizer	SPECIAL
TREFOIL	Radioactive	PRECAUTIONS

#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals			
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TD <sub>Io</sub>	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a symptom			
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects			
TC, TCo, LCio, & LCo				
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TLm	Median threshold limit			
log Kow or log Koc	Coefficient of Oil/Water Distribution			

#### REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	DOT U.S. Department of Transportation			
TC	Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NDSL	NDSL Canadian Non-Domestic Substance List			
PSL Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			
WGK	WGK Wassergefährdungsklassen (German Water Hazard Class)			

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(A)</b>	<b>(2)</b>		$\odot$	<b>(49)</b>		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$	KI COLONIA		$\Diamond$		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment