

Product Features:

- Smallest Form Factor in Mogul-Base Category
- Integrated 4kA/4kV Surge Protection
- Step-Down Thermal Management Protection
 - Wattage step-down circuit automatically prevents overheating due to high increases in ambient temperatures. Wattage returns to normal as temperatures decrease.
- Omni-directional
- Rated for Fully Enclosed Fixtures
- Wet Location Approved
- Special Adapter Transforms Base from E26 to E39
- Direct Retrofit for HID & CFL Fixtures — For use in:
 - Low Bays
 - Flood Lights
 - Wall Packs
 - Post Tops
 - And More!

Product Specifications:

Power: 36 Watts
 Lamp Lumen Output: Up to 4,680 Lumens
 Lamp Efficacy (lm/W): Up to 130 Lumens per Watt
 Selectable Kelvin: 3000K, 4000K, 5000K
 Dimensions:
 (E26) 3.35"Ø x 7.95"
 (EX39) 3.35"Ø x 8.46"
 CRI: >80
 Input Voltage: 120–277 VAC
 Life Span: 50,000 Hours
 Beam Angle: 300°
 Base Types:
 S-M (E26 with E39 adapter)
 EX39
 Operating Temperature: -4 ~ 149°F (-20 ~ 65°C)
 Power Factor: >0.95
 Total Harmonic Distortion (THD): < 20%

Available Accessories:



Daylight / Occupancy
ESL-3DHOC-LV



EXCLUSIVE
 E39-E26 Adapter Included
 with Lamps up to 55 Watts

Project: _____ Date: _____
 Catalog #: _____
 Notes: _____



SELECTABLE KELVIN
 3000K, 4000K or 5000K

KELVIN
 SELECTABLE



No Fans



No Noise



No Bugs



Ordering Guide:

ESL	TYPE	WATTAGE	GENERATION	ADJUSTABLE KELVIN	BASE
ESL	CL (CL) Corn Light	36W 36 Watts	5 (5) 5th Generation	3050 3000K, 4000K, 5000K	vv (S-M) E26 (EX39) EX39

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	SELECTABLE KELVIN
ESL-CL-36W-53050-S-M ESL-CL-36W-53050-EX39	36	4,680	130	3000K, 4000K, 5000K
ESL-CL-46W-53050-S-M ESL-CL-46W-53050-EX39	46	5,980	130	3000K, 4000K, 5000K
ESL-CL-55W-53050-S-M ESL-CL-55W-53050-EX39	55	7,150	130	3000K, 4000K, 5000K
ESL-CL-80W-53050-EX39	80	10,400	130	3000K, 4000K, 5000K
ESL-CL-120W-53050-EX39	120	15,600	130	3000K, 4000K, 5000K

Product Dimensions:

