

ATGBICS 8960-2612-C network transceiver module Fiber optic 16000 Mbit/s SFP+

Brand: ATGBICS Product code: 8960-2612-C

Product name: 8960-2612-C

Arceics
Re of the Approximation of the Approximatio

IBM Compatible Transceiver, SFP+ 16G Long Wave Fibre Channel, 10km, DOM

ATGBICS 8960-2612-C network transceiver module Fiber optic 16000 Mbit/s SFP+:

ATGBICS 8960-2612 16GBase Long Wave Fibre Channel SFP+ supports a distance of up to 10km via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of IBM 8960-2612= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards. ATGBICS 8960-2612-C. SFP transceiver type: Fiber optic, Maximum data transfer rate: 16000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Power	
Maximum data transfer rate * 16	Fiber optic 16000 Mbit/s SFP+ LC 10000 m 16 Gigabit Ethernet	Power consumption (typical)	1 W
		Operational conditions	
Interface type * Fiber optic connector Maximum transfer distance Ethernet interface type Digital Diagnostics Monitoring (DDM)		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Features		Weight & dimensions	
Product colour Silver Housing material Metal Plug and Play Hot-swap	Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 19 g	
Easy to install	✓ United Kingdom IBM	Packaging data	
Country of origin Brand compatibility		Number of products included Package type	1 pc(s) Box
Power		Technical details	
Input voltage Maximum voltage	3.3 V 3.5 V	Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.