



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 61169-65

**Documents**

Assembly instruction MA\_P9A

**Material and plating**

**Connector parts**

Outer conductor	Brass	Gold, min. 0.5µm
Coupling nut	Stainless steel	Passivated

**Technical Data Sheet****Rosenberger**

RPC-1.35

Connector straight  
Plug**P9S101-270E****Electrical data**

Impedance	50 $\Omega$
Frequency	DC to 90 GHz
Return loss	$\geq 23$ dB, DC to 26.5 GHz $\geq 20$ dB, 26.5 GHz to 50 GHz $\geq 18$ dB, 50 GHz to 90 GHz
Outer contact resistance	$\leq 2$ m $\Omega$
Test voltage	500 V
Working voltage	150 V
RF-leakage	$\geq 90$ dB up to 1 GHz

*- Limitations are possible due to the used cable type -***Mechanical data**

Mating cycles	$\leq 50$
Maximum torque	1.65 Nm
Recommended torque	0.90 Nm

**Environmental data**

Temperature range	- 40 °C to +85 °C
RoHS	compliant

**Tooling**

Tool	P9W001-000 P9W002-000
------	--------------------------

**Suitable cables**

Recommended	UT-047-TP
-------------	-----------

**Packing**

Standard	1 pce in bag
Weight	2.2 g/pce

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH &amp; Co. KG

RF\_35/09;14/6.2

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	14.12.17	Lars Ramtke	09.12.19	d00	19-2148	Marion Striegler	09.12.19
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2