



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 22.74 g ± 10%

| Connector dimension |          |
|---------------------|----------|
| Dim                 | Nominal  |
| ØS                  | 29.4 Max |
| Z                   | 31 Max   |
| VV THREAD           | M18x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D513Z26SCL**

|   |                                     |                                |                               |
|---|-------------------------------------|--------------------------------|-------------------------------|
| A   | 19-10-2016                          | First Release                  |                               |
| ISS   | DATE                                | Latest modification - by       | MOD N°                        |
| Designed By:  |                                     | Date:                          | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>  |                                     | Aluminium Plug 8D series       |                               |
| SCALE   | NA                                  | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b> |
| <b>SOURIAU</b>  |                                     | <b>WWW.SOURIAU.COM</b>         |                               |
| This document is the property of SOURIAU it must not be reproduced or communicated without permission |                                     |                                |                               |
| FORMAT  | <b>SOURIAU DRG N° 8D513Z26SCL-C</b> |                                | SHEET<br>1/2                  |

|                |                         |   |   |    |   |    |   |   |   |                                    |
|----------------|-------------------------|---|---|----|---|----|---|---|---|------------------------------------|
| BASIC SERIES:  | 8D                      | 5 | - | 13 | Z | 26 | S | C | L | Delivered W/O Contacts             |
| SHELL TYPE :   | Plug with RFI Shielding |   |   |    |   |    |   |   |   | ORIENTATION : C                    |
| CONTACT TYPE : | Standard Crimp Contact  |   |   |    |   |    |   |   |   | CONTACT TYPE : SOCKET(500 Matings) |
| SHELL SIZE :   | 13                      |   |   |    |   |    |   |   |   | CONTACT LAYOUT : 13-26             |
| PLATING :      | Z = Black Zinc Nickel   |   |   |    |   |    |   |   |   |                                    |

Contact Layout

26



2#12  
6#22D

| 13-26 |       |       |
|-------|-------|-------|
| Ctc   | X     | Y     |
| A     | 0     | 3.47  |
| B     | 2.47  | 4.34  |
| C     | 2.47  | -4.34 |
| D     | 0     | -3.47 |
| E     | -2.47 | -4.34 |
| F     | -2.47 | 4.34  |
| 1     | 3.25  | 0     |
| 2     | -3.25 | 0     |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

PN: 8D513Z26SCL

|                |                                     |                            |   |
|----------------|-------------------------------------|----------------------------|---|
| A              | 19-10-2016                          | First Release              |   |
| ISS            | DATE                                | Latest modification - by   | MOD N°  |
| Designed By:   |                                     | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Plug 8D series            |                            |   |
| SCALE          |                                     | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                     | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>              |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D513Z26SCL-C</b> |                            | SHEET 2/2   |