


		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1		RELEASED	16MAR2020	J. HEAD	DH



NOTES: UNLESS OTHERWISE SPECIFIED

1. RECEPTACLE MATERIAL:


SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER


2. BACKSHELL MATERIAL:

SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. APPLY BACKSHELL TO CABLE OD SIZE: Ø11.20-Ø19.30 . CAN BE USED WITH OR WITHOUT BUSHING.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
 - 6.3 MATING PART(S).
 - 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





	AHDM04-1	HD34-18	B-20PE-05	9				
	PART N			DE	SCRIPTION		ITEM	
QUANTITY	MATERIA			IΑ	LS LI	ST		
UNLESS OTHER		SIGNATURI	S DAT	E	Λ	mnhc	nol	
2) Tolerances are a	1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64 2 PL DEC ±0.15 Angles ±1* 3) Note reference = X		16MAR2	020	$\overline{}$	mphe		
2 PL DEC ±0.15 3 PL DEC ±0.08					Sine Systems - www.amphenol-sine.com 44724 Morley Drive			
				-L		Clinton Township, MI 48	036	
MATERIAL SPECIFICA	TIONS:	CUSTOMER:		_ [AHDM RECEPT,	- /	THD,
PROCESS SPECIFICAT	DDOCEOU ODEOUEIOATIONIO		ED FOR IGN FEATURES			// CABLE CLAMP E		
PROCESS SPECIFICATIONS.		SHOWN HEREON ARE TH THE AMPHENOL CORPOR OF REPRODUCTION ARE	PECIFICATIONS AND PERFORMANCE DATA HOWN HEREON ARE THE PROPERTY OF HE AMPHENOL CORPORATION. NO RIGHTS IF REPRODUCTION ARE IMPLIED. ALL IMPNSIONS ARE SILBJECT TO NORMAL		B C-	AHDM04-18-2		A1
NEXT ASS'Y:	NEXT ASS'Y:		IONS.	S	NONE		sheet 1 of	1

2-059 REV: A1 SH: 1

KIT, RECPT AND BACKSHELL, SZ 18

ATM Series™ - Contact Size 20 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-010-2031	Male Contact - Pin, Gold-plated	20	16-18	Machined	
AT62-005-20141	Female Contact - Socket, Gold-plated	20	16-18	Machined	
AT60-010-20141	Male Contact - Pin, Nickel-plated	20	16-18	Machined	
AT62-005-2031	Female Contact - Socket, Nickel-plated	20	16-18	Machined	
AT60-202-2031	Male Contact - Pin, Gold-plated	20	20-22	Machined	
AT62-201-2031	Female Contact - Socket, Gold-plated	20	20-22	Machined	
AT60-202-20141	Male Contact - Pin, Nickel-plated	20	20-22	Machined	
AT62-201-20141	Female Contact - Socket, Nickel-plated	20	20-22	Machined	

Tooling - Machined Contacts				
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

Contact Removal Tools				
Part	Part Number	Description		
from hard	ATRT-100	Used for removal of contacts for A Series™ products		
	AT11-240-2005	Contact Removal Tool, Plastic, Size 20		
	AT13-204-2005	Sealing Plug, Size 20, White		

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-20-0144	Male Contact - Pin, Gold-plated	20	16-22	Stamped & Formed		
AT62-20-0144	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT60-20-0244	Male Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT62-20-0244	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT60-20-0122	Male Contact - Pin, Nickel-plated	20	16-22	Stamped & Formed		
AT62-20-0122	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT60-20-0222	Male Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT62-20-0222	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT60-20-0277	Male Contact - Socket, Tin-plated	20	16-22	Stamped & Formed		
AT62-20-0277	Female Contact - Socket, Tin-plated	20	16-22	Stamped & Formed		
AT60-20-0422	Male Contact - Socket, Nickel-plated	20	20-22	Stamped & Formed		
AT62-20-0444	Female Contact - Socket, Gold-plated	20	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number	Description			
	MFX-3974	Crimp Die - Size 20 (\$&F contacts only)			
	MFX-3976	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -04XX Series			
	MFX-3978	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -02XX Series			
	ATT-20-00	Hand Crimp Tool - Size 20, 20AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins					
Part Number Description		Size	AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined	

Tooling - Machined Contacts				
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

Contact Removal Tools					
Part	Part Number	Description			
3	ATRT-100	Used for removal of contacts for A Series™ products			
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16			
	A114017	Sealing Plug, Size 16, White			

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Type		
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed		
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed		
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed		
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed		
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed		
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed		
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed		
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed		
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed		
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed		
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed		
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed		
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed		
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed		
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed		
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number	Description			
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)			
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)			
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)			
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)			
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)			
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)			
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021