




REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A1	-	RELEASED	23SEP2021	JAH	DH		





AMPHENOL

20.3



NOTES: UNLESS OTHERWISE SPECIFIED 1. MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: END CAP; REDUCED DIA. WIRE SEAL

- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 25 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

12 - 14 AWG

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP04-4P* RECEPTACLE (* = MODIFICATIONS AND COLORS)

2.46 mm

(.097 in)

12

5. ALL D

4.01 mm

(.158 in)

		AR SEAL WII	
CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
			WIRE RANGI

MODIFICATIONS AND COLORS)						PART NUMBER
DIMENSIONS ARE FOR REFERENCE USE ONLY.						ATP06-4S-MM01
ITACT SIZE AND REAR SEAL WIRE RANGE:						ATP06-4S-MM01BLK
NIACI	SIZE AND RE	AN SEAL WII	NE RANGE.			
NTACT	MIN. INSUL	MAX. INSUL	TYPICAL	STANDA	RD MOLDED	COLOR IS GREY. AD
IZE OD OD WIDE BANGE				COLOR (BLACK) IS	AVAILABLE VIA SPEC

OR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

PART NUMBER CHART

REQUIRES CONTACT RETENTION WEDGE AWP-4S	ТП-PLUG, 4 SOCKET,ATP SERIES,REDUCED DIA. WIRE SEAL,END CAP
REFER TO PART NUMBER CHART FOR AVAILABLE CONNECTOR COLORS— END CAP. COLOR: BLACK	END CAP DWG NO: ATPO6-4S-MM01XXX REV: A1 SH: 1

	SEE PART NUMBER CHART		HART						
	PART NUMBER					DE	SCRIPTION		ITEM
QUANTITY MATER					٩LS	S LI	ST		
UNLESS OTHER 1) All dimensions a		SIGN	ATURES	DATE		$\overline{\Lambda}$	mnho	nal	
2) Tolerances are a		DRAWN:	JHEAD	23SEP21			mphe		
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.com 44724 Morley Drive				
3) Note reference	= <u>x</u>	ENGINEER:							
MATERIAL SPECIFICA	TIONS:	APPROVAL:	DH	23SEP21	Clinton Township, MI 48036				
		CUSTOMER:					G, 4 SOCKET, ATP		
PROCESS SPECIFICATIONS: NEXT ASSY:			S IS SUPPLIED F ONLY. DESIGN		RED	UCED	DIAMETER WIRE S	SEAL, END C	CAP
		SHOWN HERE THE AMPHENO OF REPRODUC	NS AND PERFO ON ARE THE PR OL CORPORATIO CTION ARE IMPL ARE SUBJECT TO	ROPERTY OF ON. NO RIGHTS LIED. ALL	B	C-	ATP06-4S-MM		A1
			ING VARIATION	IS.	SCALE: N	ONE	s	SHEET 1 OF	1

ATP Series™ - Contact Size 12 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined	
AT62-203-12141-10	Female Contact - Socket, Nickel-plated	12	10-12	Machined	
AT60-220-1231	Male Contact - Pin, Gold-plated	12	12-14	Machined	
AT62-210-1231	Female Contact - Socket, Gold-plated	12	12-14	Machined	
AT60-204-12141	Male Contact - Pin, Nickel-plated	12	12-14	Machined	
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined	

DiagnosticGrade™ Machined Contacts, Sockets & Pins • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective					
Part Number	Description	Size	AWG	Туре	
65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined	
AT62-210-1231-1820	Female Contact - DiagnosticGrade™, Socket, Gold-plated	12	20	Machined	

	Tooling - Machined Contacts				
Part	Part Number	Description			
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)			
550	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)			
0,	M300-25A	Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG (Machined contacts only)			
	MFX-3966	Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG (Machined contacts only)			

Contact Removal Tools					
Part	Part Number	Description			
	ATRT-100	Used for removal of contacts for A Series™ products			
	AT11-337-1205	Contact Removal Tool, Plastic, Size 12			
	A114017	Sealing Plug, Size 12, White			

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed		
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed		
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed		
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed		
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed		
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed		
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed		
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number	Description			
	MFX-3973	Crimp Die - Size 12 (S&F contacts only)			
	MFX-3985	Crimp Die - Svize 12 (S&F contacts only) 10-12AWG -02XX Series			
	ATT-12-00	Hand Crimp Tool - Size 12, 12AWG (S&F contacts only)			
	ATT-12-01	Hand Crimp Tool - Size 12, 10AWG (S&F contacts only)			