



LA78-3/8X16:40-ZS

Ruland Adjustable Clamping Lever, Lever Length 78mm, Stud Thread 3/8X16, Stud Length 40mm, Zinc Lever, Stainless Steel Inserts




Description

Ruland LA78-3/8X16:40-ZS is an adjustable clamping handle with a 78mm handle, 3/8X16 threaded stud, 40mm stud length, 16mm insert diameter, and 55mm overall height. The stainless steel inserts combined with a zinc die-cast handle allow for use in corrosive applications where durability is required. LA78-3/8X16:40-ZS has a textured finish on the handle making it easy for the user to grip in environments with water, coolant, chemicals, or other liquids. It is commonly found in packaging, printing, food processing, and manufacturing systems where conveyor rails, sensors, screens, and other components require frequent adjustments without the use of tools. The adjustable feature of this handle allows it to be used in confined spaces with limited hand access or where 360 degree rotation is not possible. Serrations connect the insert to the handle for easy disengagement. The user pulls the handle upwards by hand to disengage the serrations allowing it to be swiveled to the desired clamping position. Serrations automatically re-engage once the user releases the handle locking it in-place. A 3/8X16 threaded stud can replace existing hardware in an application or mate to an equivalently sized tapped hole for a quick installation. LA78-3/8X16:40-ZS is black to seamlessly integrate with the aesthetics of most equipment. It is manufactured by Otto Ganter, stocked by Ruland, and RoHS3 and REACH compliant.

Product Specifications

Thread (TH)	3/8 in - 16 TPI	Stud Length LS	40 mm
Lever Length L1	78 mm	Overall Height H1	55 mm
Hub Height H2	36 mm	Hub Diameter DH	21 mm
Handle Disengagement Travel H3	4 mm	Sleeve Length L2	8 mm
Sleeve Diameter D1	16 mm	Handle Material	Zinc
Handle Color	Black	Insert and Screw Material	303 Stainless Steel
Weight (lbs)	0.330200	Manufacturer	JW Winco/ Otto Ganter
UPC	634529236932	Country of Origin	Germany
Tariff Code	8487.90.0080	UNSPC	31162807

Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.

Prop 65  **WARNING** This product can expose you to chemicals including Soots, Benzene, Lead, and Nickel (metallic), known to the State of California to cause cancer, and Lead and Benzene known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.