

ZCE07

Limit switch head, Limit switches XC Standard, ZCE, spring rod lever termoplastic end nitrile boot



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

| | |
|---------------------------|--|
| Range of Product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or Component Type | Limit switch head |
| Device short name | ZCE |
| Head type | Multi-directional head |
| Product Compatibility | XCKP XCKT XCMD XCKD |

| | |
|----------------------------|--|
| Associated body | ZCT27N12 ZCD28 ZCP37 ZCMD29L5 ZCMD39L2 ZCT21N12 ZCP25 ZCMD37L1 ZCMD29C12 ZCT21G11 ZCMD21L1 ZCMD29L1 ZCT26N12 ZCD31 ZCMD37L2 ZCMD21C12 ZCT27P16 ZCD35 ZCMD21L5 ZCD29 ZCMD25L2 ZCMD81L1 ZCMD29L2 ZCP27 ZCT28G11 ZCMD39L1 ZCP28 ZCT27G11 ZCMD21L2 ZCP29M12 ZCMD21M12 ZCP35 ZCT21P16 ZCT25N12 ZCMD41L2 ZCMD81L2 ZCD25 ZCP31 ZCMD21L08R12 ZCP21 ZCD27 ZCD37 ZCP39 ZCMD25L5 ZCMD37L5 ZCT25G11 ZCD26 ZCP21M12 ZCMD61M12 ZCT28P16 ZCT25P16 ZCD39 ZCD21 ZCT28N12 ZCP29 ZCMD61C12 ZCMD41L5 ZCMD81L5 ZCMD25L1 ZCT26G11 ZCMD39L5 ZCD21M12 ZCT26P16 ZCMD21L08U78 ZCD29M12 ZCMD41L1 ZCP26 ZCMD69C12 |
| Movement of operating head | Multi-directional |
| Type of operator | Spring rod spring return metal with nitrile boot and thermoplastic end) |
| Type of approach | Multi-directional approach |

Complementary

| | |
|------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without |

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Environmental characteristic | Standard environment |

Ordering and shipping details

| | |
|-----------------------|--------------------------------------|
| Category | 22413 - LIMIT SWITCH, IEC, MINIATURE |
| Discount Schedule | T |
| GTIN | 3389110191080 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.67 oz (19 g) |
| Returnability | Yes |
| Country of origin | ID |

Packing Units

| | |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.63 in (1.6 cm) |
| Package 1 width | 0.63 in (1.6 cm) |
| Package 1 Length | 4.96 in (12.6 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|