


TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	(1)







.X±0.25.XX±0.13.XXX±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


SHELL:STEEL, NICKEL PLATEDCONTACT:COPPER ALLOY, 30µ" GOLD PLATEDOPERATING TEMPERATURE:-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

POWER/CO-AX CONTACT RATING:30A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

1000V AC rms



COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
		DRAWN: C.B	DATE: JAN. 01/20	19
			DATE:	
EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
		DRAWING NUMBER: 629-2WK	2650-3N2	ISSUE
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 629-2WK	2650-3N2	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

