











Ν	O	Т	E	S	

MATERIAL:	
HOUSING:	
SHELL:	
CONTACT:	

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING: 40A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. **INSULATOR RESISTANCE:**

DIELECTRIC WITHSTANDING VOLTAGE:



1000V AC rms

-55°C ~ 125°C



				SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATIO	DRAWN: C.B	DATE: JAN. 01/20	19				
			DATE:				
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2			
TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-2W2	-640-4TA	ISSUE			
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-2W2	-640-4TA	1			



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

W REFERENCE NO.: 630	COMBO ASSEMBLY
RAWN: C.B	DATE: JAN. 01/2019
CHECKED:	DATE:
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2
RAWING NUMBER: 630-2W2	2-640-4TA ISSUE
PART NUMBER: 630-2W2	2-640-4TA 1

