

NOTES:

MATERIAL: HOUSING:	THERMOP
SHELL: CONTACT:	STEEL, NIC COPPER A
OPERATING TEMPERATURE:	-55°C ~ 12

.X ±0.25 .XX ±0.13


.XXX ±0.05

10.70

5.80

POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



PLASTIC POLYESTER, UL94V-0 ICKEL PLATED ALLOY, GOLD FLASH PLATED


25°C

20A (CURRENT)

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

5000MΩ min.

1000V AC rms



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
		DRAWN: C.B	DATE: JAN. 01/20	19
		CHECKED:	DATE:	
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
TORONTO, ONTARIO CANADA	CANADA OR USED AS THE BASIS FOR THE		DRAWING NUMBER: 630-3WK3240-2N1	
YOUR CONNECTION TO QUALITY & SERVICE MANUFACTURE OR SALE OF APPAR WITHOUT WRITTEN PERMISSION.		PART NUMBER: 630-3WK	3240-2N1	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



