ſ	ד ם <u>ד</u>		0	Þ	
4					4
ω	Keying Shown as example		LAYOUT SHOWN AS EXAMPLE		3
	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
N	-Shell Material : Aluminium ØS 35.7 Max -Shell Plating : Olive drab Cadmium Z 31 Max -Insulator : Thermoplastic VV THREAD M25x1-6g -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Sumphility -Source		SOURIAU shall not be liable for any non-conforr due to a use of the Products which does not the Specifications issued by either of the Parties o (professional recommendation, technical Country Jur FR	comply with r by a third party	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	PN: 8D517W06AB			
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	A 17-10-2016	5 First Release		_
_	-Mass : 29.9 g ± 10%	ISS DATE	Latest modification - by		
	Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Plug 8D series				
_ _	BASIC SERIES: 8D 5 - 17 W 06 A B SHELL TYPE : Plug with RFI Shielding - 17 W 06 A B	SCALE	General linear Tolerances: ±	NPRDS / PROJECT 859	-
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-06	FORMAT	SOURIAU DRG N		_
		A3	8D517W06AB-C	1/2	
	H G F E	D	C B	A	

r	т	۵	г –	m	Ū	0
		Contact Layout				
4	-x ($ \overset{+Y}{\stackrel{E_{\bigoplus}}{\bigoplus}} \overset{A_{\bigoplus}}{\bigoplus} $				
		Contacts (insert arrangement 17-6)				
ω	Conta position A B C C D E F	Location X-axis Y-axis (mm) (mm) +.121 (3.07) +.209 (5.31) +241 (6.12) +.000 (0.00) -0.000 (0.00) 241 (6.12) -241 (6.12) +.000 (0.00) 121 (3.07) +.209 (5.31)				
ŭ	Shell Arrangement Nur size no. co	where of ntacts Size contacts Service rating f Contact location Supersedes 6 12 I All MtS20053-6				
	\vdash				[SOURIAU shall not be liable for an
						due to a use of the Products w the Specifications issued by either o (professional recommenda
N						PN: 8D517
					A 17-10-20	016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					SCALE	Alumir General linear
_					NA	Tolerances:
					FORMAT	
		-			A3	SOURIAU 8D517W
	Н	G	l F	E	D	C

σ		А					
				4			
				3			
any non-conformi which does not co or of the Parties or l idation, technical n intry Jurisc	mply with by a third party	List		2			
7W06AB							
	CUSTOMER DF		10D N°				
ninium Plug 8D series							
ar	NPRDS / PROJECT 859						
J.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission							
U DRG N° SHEET W06AB-C 2/2							
В		Α					