


## C905U151KYYDBA7317

Not for New Design

C900AC SFTY X1-400 Y2-250, Ceramic, 150 pF, 10%, 400 VAC (X1), 250 VAC (Y2), Y5P, Lead Spacing = 5mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click here for the 3D model.

Dimensions	
D	7mm MAX
Т	5mm MAX
S	5mm +/-0.8mm
НО	18mm +2/-0mm
F	0.55mm +/-0.1mm

Packaging Specifications	
Packaging	Ammo
Packaging Quantity	1000

General Information				
Series	C900AC SFTY X1-400 Y2-250			
Style	Radial Disc			
RoHS	Yes			
Termination	Tin			
Failure Rate	N/A			
Qualifications	UL, ENEC, VDE, CSA, CAN			
AEC-Q200	No			
Halogen Free	Yes			
Component Weight	700 mg			

Specifications				
Capacitance	150 pF			
Capacitance Tolerance	10%			
Voltage AC	400 VAC (X1), 250 VAC (Y2)			
Dielectric Withstanding Voltage	2600 VDC			
Temperature Range	-40/+125°C			
Temperature Coefficient	Y5P			
Dissipation Factor	2.5%			
Insulation Resistance	10 GOhms			
Safety Class	X1/Y2			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.