

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC

Θ


6

0

WITHSTANDING VOLTAGE:

5000MΩ min.

1000V AC rms



(1)

|              | COMBINATION D-SUB          |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                  |       |
|--------------|----------------------------|--|--------------------------------------|------------------|-------|
|              |                            |  | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|              |                            |  | CHECKED:                             | DATE:            |       |
| EDAC         | EDAC INC                   | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|              | TORONTO, ONTARIO<br>CANADA |  | DRAWING NUMBER: 630-17W              | 5650-3TE         | ISSUE |
| YOUR CONNECT | TION TO QUALITY & SERVICE  |  | PART NUMBER: 630-17W                 | 5650-3TE         | 1     |



0 6

0

0

