E E E E E E E E E E E E E E E E E E E	m m		0	₩	Þ	7
4	ØS					4
ω			LAYOUT SHOWN AS E	KAMPLE		3
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite	DimNominalØS44.9 Max					\vdash
-Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z' 31.5 Max VV THREAD M34x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Countr		List	
 Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles 			FR Not Listed			2
-Delivered with Souriau contacts and Accessories			PN: 8D523M35SN			
-Temperature Range : -65°C to +200°C			L6 First Release			_
-Salt Spray : 2000 hours						
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DI	MOD N°	
		TITLE	Composite Plug 8D series			
BASIC SERIES: 8D 5 - 23 M	Л 35 S N	SCALE	General linear Tolerances:	NPRDS / PR	OJECT	_
SHELL TYPE : Plug with RFI Shielding				This docume	ent is the property of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 23	CONTACT TYPE : SOCKET(500	ATION : N Matings)	J WWW.SOURIAU.C	OIVI it must not	SOURIAU t be reproduced or ed without permission	
PLATING : M = Nickel	CONTACT LAYO		SOURIAU		SHEET	_
		A3	8D523M		1/2	
		1				

