

PRODUCT DATASHEET FP16391_FLORENTINA-HLD-BW

FLORENTINA-HLD-BW

~60° batwing beam

TECHNICAL SPECIFICATIONS:

Dimensions	285.6 x 19.5 mm
Height	10.2 mm
Fastening	clips
ROHS compliant	yes 🛈



MATERIAL SPECIFICATIONS:


Component	Туре	Material	Colour	Finish
TINA-BW	Single lens	PMMA	clear	
FLORENTINA-HLD	Holder	PC	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FP16391_FLORENTINA-HLD-BW	Single lens	160	32	16	3.6
» Box size: 398 x 298 x 140 mm					




PRODUCT DATASHEET FP16391_FLORENTINA-HLD-BW



See also our general installation guide: www.ledil.com/installation_guide



PHOTOMETRIC DATA (MEASURED):





PRODUCT DATASHEET FP16391_FLORENTINA-HLD-BW

PHOTOMETRIC DATA (SIMULATED):


CREE ≑		90 ⁺ 90 ⁺
LED	J Series 3030	
FWHM / FWTM	Asymmetric	75.
Efficiency	79 %	400
Peak intensity	1.3 cd/lm	
LEDs/each optic	1	
Light colour	White	a1. a2.
Required components:		800
C14446_FLORENTI		
		30* 30*
		15° 0° 15°
CREE ≑		90°
LED	J Series 3030	
FWHM / FWTM	Asymmetric	
Efficiency	91 %	60° 400 60°
Peak intensity	1.3 cd/lm	
LEDs/each optic	1	
Light colour	White	43.* 800
Required components:		
		30* 30*
		45° 0° 15°
MICHIΛ		90°
LED	NCSxE17A	
FWHM / FWTM	Asymmetric	
Efficiency	94 %	60°. 400 60°
Peak intensity	1.3 cd/lm	
LEDs/each optic	1	
Light colour	White	65° 62°
Required components:		
C14446_FLORENTI	NA-SHD	
		1200
		36* 36* 36*
Μ ΝΙCΗΙΛ		20° 20°
LED	NVSxE21A	
FWHM / FWTM	Asymmetric	10
Efficiency	94 %	400
Peak intensity	1.3 cd/lm	60*** 00*
LEDs/each optic	1	
Light colour	White	er av
Required components:		
C14446_FLORENTI		



PHOTOMETRIC DATA (SIMULATED):

OSRAM Opto Semiconductors

LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour Required components: OSLON Square EC Asymmetric 88 % 0.8 cd/lm 1 White





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy