

i110-RA313

ELECTRO-MECHANICAL SAFETY SWITCHES



i110-RA313 | i110R ELECTRO-MECHANICAL SAFETY SWITCHES



Ordering information

Туре	Part no.
i110-RA313	6025107

Other models and accessories -> www.sick.com/i110R


Detailed technical data


Features	
Number of positive action N/C contacts	3
Number of N/O contacts	1
Actuation frequency	≤ 6,000 /h
Actuation torque	≥ 0.34 Nm
Actuation directions	4
Approach speed	0.1 m/min 15 m/min
Positive break angle	44°
Safety-related parameters	
B _{10d} parameter	2×10^{6} switching cycles (with small load)
Туре	Type 1 (EN ISO 14119)
Actuator coding level	Uncoded (EN ISO 14119)
Safe state in the event of a fault	The switch has no internal fault detection and is unable to assume a safe state in the event of a fault. Fault detection is performed by the connected safety-related logic unit.
Functions	
Safe series connection	No
Interfaces	
Connection type	Cable gland, 1 x M20
Conductor cross-section	≤ 2.5 mm²
Electrical data	
Switching principle	Slow action switching element
Usage category	AC-15/DC-13 (IEC 60947-5-1)
Rated operating current (voltage)	3 A (240 V AC) 3 A (24 V DC)
Rated insulation voltage U _i	250 V
Rated impulse withstand voltage $\mathbf{U}_{\mathrm{imp}}$	2,500 V AC
Short-circuit protection	F15

i110-RA313 | i110R ELECTRO-MECHANICAL SAFETY SWITCHES

Curitada a cura la co	≥ 5 V DC
Switching voltage	
Switching current (switching voltage)	≥ 5 mA (5 V DC)
Mechanical data	
Weight	0.52 kg
Housing material	Zinc diecast
Surface treatment	Varnished
Mechanical life	10 x 10 ⁶ switching cycles
Ambient data	
Enclosure rating	IP66 (IEC 60529)
Ambient operating temperature	-25 °C +80 °C
Storage temperature	-25 °C +80 °C
Classifications	
ECI@ss 5.0	27272601
ECI@ss 5.1.4	27272601
ECI@ss 6.0	27272601
ECI@ss 6.2	27272601
ECI@ss 7.0	27272601
ECI@ss 8.0	27272601
ECI@ss 8.1	27272601
ECI@ss 9.0	27272601
	EC001829
ETIM 5.0	
ETIM 5.0 ETIM 6.0	EC001829


Dimensional drawing (Dimensions in mm (inch))





i110-RA313 | i110R ELECTRO-MECHANICAL SAFETY SWITCHES

Actuator travel diagram



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

