ATGBICS JD094B-BX-U H3C Compatible Transceiver SFP+ 10GBase-BX-U (Tx1270nm/Rx1330nm, 10km, SMF, DOM, Ind Temp)

Brand : ATGBICS

Product code: JD094B-BX-U-C

Product name : JD094B-BX-U H3C Compatible Transceiver SFP+ 10GBase-BX-U (Tx1270nm/Rx1330nm, 10km, SMF, DOM, Ind Temp)

JD094B-BX-U H3C Compatible Transceiver SFP+ 10GBase-BX-U (Tx1270nm/Rx1330nm, 10km, SMF, DOM, Ind Temp)


ATGBICS JD094B-BX-U H3C Compatible Transceiver SFP+ 10GBase-BX-U (Tx1270nm/Rx1330nm, 10km, SMF, DOM, Ind Temp):

ATGBICS JD094B-BX-U 1000Base-BX SFP supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of Tx1270nm/Rx1330nm via an LC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. This product is suitable for rugged environments and can operate at temperatures between -40C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of H3CJD094B-BX-U= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





| Performance | | Power | |
|---|---|--|--|
| SFP transceiver type * Maximum data transfer rate * Interface type * | kimum data transfer rate *10000 Mbit/sprface type *SFP+gle-mode fiber (SMF) supported✓ti-mode fiber (MMF) supported✓er optic connectorLCtransceiver standardBX-Ukimum transfer distance10000 mwavelength (max)1270 nmwavelength (max)1330 nmernet LAN✓ernet interface type10 Gigabit Ethernet | Input voltage Maximum voltage Power consumption (typical) | 3.3 V 3.5 V 1 W |
| Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Tx wavelength (max) Rx wavelength (max) | | Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | -40 °C 185 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95% |
| Ethernet interface type Digital Diagnostics Monitoring (DDM) | | Weight & dimensions Width Depth | 13.4 mm 56.5 mm |
| Features Product colour Housing material | Silver Metal United Kingdom H3C CE, FCC, RoHS | Height Weight Packaging data | 8.5 mm 19 g |
| Plug and Play Hot-swap Easy to install Country of origin | | Number of products included Package type Technical details | 1 pc(s) Box |
| Brand compatibility Certification | | Sustainability compliance Sustainability certificates Doesn't contain | ✔ RoHS Lead |



5056468719980

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.