HellermannTyton

Specification Sheet

Part Number: 184-22055

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High-Density Slotted-Wall Wiring Duct, 4" x 3", Non-Adhesive, PVC, Intrinsic Blue, 120 ft/ctn

Article Number 184-22055

Type SLHD4X3

Color Intrinsic Blue (IBU)

Quantity Per carton

Product Description Manufactured from the same PVC material as standard Pro-Duct

colors, HellermannTyton also offers an intrinsic blue color option. The intrinsic blue color indicates that the wiring contained in the duct runs to intrinsically safe components in the control panel. HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description	High-Density Slotted-Wall Wiring Duct, 4" x 3", Non-Adhesive, PVC, Intrinsic Blue, 120 ft/ctn
Global Part Name	SLHD4X3-PVC-BU
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	4.0
Width W (Metric)	101.6
Height H (Imperial)	3.07
Height H (Metric)	77.9
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Halogen Free	No

No

+122°F (+50°C)

UV Resistant (Yes/No)

Operating Temperature

Reach Compliant (Article 33)

ROHS Compliant

Yes

Certification/Specification

CSA UL EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A

Yes

Package Quantity (Imperial) 120.0

UL Recognized (US)

Package Quantity (Metric) 36.58

Customs Number 3925900000

 $\hbox{@\,}2023$ HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions