


50HV25N222JN

Aliases (50HV25N222J)

HV RAD-LDD Indust COG HV, Ceramic, 2200 pF, 5%, 5000 VDC, COG, Commercial, High Voltage, Lead Spacing = 14.61mm



Click here for the 3D model.

Dimensions	
L	17.02mm MAX
Н	15.24mm MAX
Т	6.89mm MAX
S	14.61mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications

Packaging	Waffle
Packaging Quantity	20

General Information	
Series	HV RAD-LDD Indust COG HV
Style	Radial
Description	Commercial, High Voltage
Features	Commercial
RoHS	With Exemptions
REACH	SVHC (Pb - CAS 7439-92-1)
Termination	Nickel
Failure Rate	N/A
AEC-Q200	No

Specifications			
Capacitance	2200 pF		
Capacitance Tolerance	5%		
Voltage DC	5000 VDC		
Dielectric Withstanding Voltage	6000 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	COG		
Dissipation Factor	0.15%		
Aging Rate	0% Loss/Decade Hour		
Insulation Resistance	100 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.