



# **Product Description**

Security & Sound Cable, Rated-CMG-FPL-PLTC, 1-16 AWG stranded tinned copper pair with PVC insulation, Beldfoil® shield, Waterblocking tape, PVC jacket

## **Technical Specifications**

### Product Overview

ble Applications:	Security System, Int	ercom/PA, Audio/Speaker, P	ower-Limited Controls, Noisy & Wet Locatio	n, Below-Grade Duc
struction Details				
uctor				
ent Number of Element		Material		
s) 1	16 AWG 7x24	TC - Tinned Copper		
tion				
ent Material	Nom. Thickness	Nom. Insulation Diameter	Color Code	
s) PVC - Polyvinyl Chlor	ide 0.010 in (0.25 mm)	0.0775 in (1.97 mm)	Black & Red	
Shield				
d Type Material	Coverage I	Drainwire Type		
Bi-Laminate (Alu		AWG (7x26) TC		
rblocking:	Waterblock Tape			
Jacket				
		liameter		
- Polyvinyl Chloride 0.037		(0.45 mm)		
Il Cable Diameter (Nomina	al): 0.254 in (6.45 mm)			
trical Characteristi	cs			
s) 4.4 Ohm/1000ft	R Nom. Capacitance 76 pF/ft (250 pF/m)	Cond-to-Cond		
	10 pi /it (200 pi /iii)			
je				
UL Voltage Rating				
/ (CMG, FPL, PLTC-ER)				
hanical Characteris	stics			
erature				

UL Temperature	Operating
105°C	-30°C to +105°C

### Bend Radius

Stationary Min.	Installation Min
2.5 in (64 mm)	2.5 in (64 mm)

Max. Pull Tension:	93 lbs (42 kg)
Bulk Cable Weight:	34 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial	
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available	
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEEE 1202	
NEC / UL Compliance:	Article 725, Article 760, Article 800, CMG, FPL, PLTC-ER	
CEC / C(UL) Compliance:	CMG	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

#### **History**

Update and Revision:

Revision Number: 0.431 Revision Date: 04-14-2023

#### **Part Numbers**

#### Variants

Item #	Color	UPC
5240F1 0021000	Black	612825158684
5240F1 0101000	Black	612825158691

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.