



NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 15µ GOLD PLATING

OPERATING TEMPERATURE: -55°C TO +125°C

**CURRENT RATING: 3A PER CONTACT** CONTACT RESISTANCE:  $25m\Omega$  MAX. **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

		SW REFERENCE NO.: 622 ASSEMBLY			
	622 SERIES D-SUB CONNECTOR		DRAWN: C.B	DATE: AUG. 01/20	)18
			CHECKED:	DATE:	
		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	1
		SHALL NOT BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 622-025-360-512		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 622-025-	360-512	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

SW REFERENCE NO.: 622 ASSEMBLY						
DRAWN: C.B	DATE: AUG. 01/2018					
CHECKED:	DATE:					
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 1					
DRAWING NUMBER: 622-025-3	360-512 ISSUE					
PART NUMBER: 622-025-3	360-512 1					