


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 30.8 |
| B | PG13,5 |
| C | 25 |
| D | 23.05 |
| E | 4 |
| F | 73 |
| G | 8 |
| H | 31.7 |
| I | 34.8 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |
| 11 | O-RING ENDGEHÄUSE / O-RING ENDBELL |
| 15 | PG-ENDGEHÄUSE / PG-ENDBELL |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: |
|--|
| Shell Material: Aluminium alloy |
| Shell Plating: Olive drab chromate over cadmium (conductive) |
| Insulator Material: CR-Elastomere |
| Contact Material: Copper alloy |
| Contact Plating: Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for CUSTOMER



description CA01PG18-3S-B-44
 Cable connecting plug
 PG-endbell with ferrule and grommet
 Solder Cup / Socket / Layout: 18-3