



## **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series 1B

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 3.50 - 3.90 mm

**Status** active

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model GMA\*: Bend relief Red

**Keying** No keying

Housing Material Thermoplastic polyurethane elastomer (Elastollan 1185 A)

Variant R: Red

Weight .80 g

#### **Performance**

Configuration

Insulator


**Rated Current** 

#### **Others**

Temp (min / max):  $-40^{\circ}$ C /  $+80^{\circ}$ C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**



No keying

### **Dimensions**

	A	L
mm.	3.5	30
in.	0,14	1,18

# **RECOMMENDED BY LEMO**

**Tools** 

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.