

USB-C to HDMI Adapter Cable (M/M), 4K, 4:4:4, Thunderbolt 3 Compatible, White, 6 ft. (1.8 m)

MODEL NUMBER: U444-006-HWE











USB-C to HDMI cable directly connects an HDMI monitor to your MacBook Pro, Windows laptop or tablet's USB-C or Thunderbolt 3 port.

Features

USB-C to HDMI Converter Connects a USB-C or Thunderbolt 3 Port to a 4K MonitorThis USB Type-C to HDMI adapter (M/M) connects an HDMI monitor, projector or television to the USB-C or Thunderbolt 3 port on your MacBook Pro or Windows laptop. It's an ideal connector for multitasking, presenting video at trade shows and conferences, editing documents, playing online games and watching movies on a larger 4K screen. No other adapter or cable is needed to complete your 4K connection. The U444-006-HWE is uni-directional and only converts from USB-C to HDMI.

Supports USB-C DisplayPort Alternate Mode for Converting Audio/Video SignalsBy connecting the USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to an HDMI monitor, television or projector without installing special software drivers.

Enjoy the Clarity of True 4K HDMI Video with Multi-Channel Audio and 4:4:4 ColorThis 4K HDMI cable supports true 4K resolutions up to 4096 x 2160 (4K x 2K) at 30 Hz. It also supports 36-bit Deep Color and 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time.

Ready to Use Right from the Package, So You Can Plug and Play Immediately The plug-and-play USB Type-C to HDMI cable requires no software or external power. Just connect the USB-C plug to the USB-C or Thunderbolt 3 port on a source device that supports USB DisplayPort Alternate Mode, and connect the HDMI plug to your display. The six-foot (1.8-meter) USB 3.1 Gen 1 cable is backward compatible with previous USB generations, so you can use it with legacy equipment.

Highlights

- Converts audio/video signals from sources supporting USB DisplayPort Alt Mode
- Supports resolutions up to true 4K @ 30 Hz (4:4:4) for crystalclear video with audio
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation
- Uni-directional 6 ft. cable directs A/V signals only from USB-C to HDMI

Applications

- Watch 4K video content from a MacBook Pro or Windows laptop on an Ultra HD television, monitor or projector
- Connect a tablet, smartphone or other USB-C source to a conference table's A/V box to give a video presentation on a large screen
- Play online or PC video games that display optimal graphics
- Link an HDTV to your PC for use as a 4K monitor

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with HDMI input

Package Includes

• U444-006-HWE USB-C to HDMI Adapter Cable, M/M, White, 6 ft.

Specifications

OVERVIEW



| UPC Code | 027222252027 | |
|--------------------------------|---|--|
| | 037332253927 | |
| Product Type | Passive Cable | |
| Technology | HDMI | |
| VIDEO | | |
| Max Supported Video Resolution | HDMI: 3840 x 2160, Including 4096 x 2160 (4K x 2K) @ 30Hz | |
| Max Supported Color Depth | 36-bit Deep Color | |
| Chroma Sub Sampling | 4:2:2; 4:4:4 | |
| INPUT | | |
| Bus Powered | Yes | |
| PHYSICAL | | |
| Color | White | |
| Material of Construction | TPE, ABS | |
| Cable Jacket Color | White | |
| Cable Jacket Material | TPE | |
| Cable Outer Diameter (OD) | 4.2mm | |
| Wire Gauge (AWG) | 34/24 | |
| Cable Length (ft.) | 6 | |
| Cable Length (m) | 1.83 | |
| Cable Length (in.) | 72 | |
| Shipping Weight (lbs.) | 0.15 | |
| Shipping Weight (kg) | 0.07 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 32° to 113°F (0° to 45°C) | |
| Storage Temperature Range | 14° to 158°F (-10° to 70°C) | |
| Operating Humidity Range | 10% to 85% RH, Non-Condensing | |
| Storage Humidity Range | 5% to 90% RH, Non-Condensing | |
| CONNECTIONS | | |
| Side A - Connector 1 | USB C (MALE) | |
| Side B - Connector 1 | HDMI (MALE) | |
| Connector Plating | Nickel | |
| Contact Plating | Gold | |



| FEATURES & SPECIFICATIONS | | |
|--|-------------------------------------|--|
| IP68 Rated | No | |
| IP20 Rated | No | |
| HDCP Specification | 1.4 | |
| Driver Required | No | |
| STANDARDS & COMPLIANCE | | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | 3-year limited warranty | |



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.