ATGBICS X4455A Sun Oracle Compatible Transceiver XFP 10GBase (850nm, MMF, 300m, DOM)

Brand : ATGBICS

Product name : X4455A Sun Oracle Compatible Transceiver XFP 10GBase (850nm, MMF, 300m, DOM)

X4455A Sun Oracle Compatible Transceiver XFP 10GBase (850nm, MMF, 300m, DOM)

ATGBICS X4455A Sun Oracle Compatible Transceiver XFP 10GBase (850nm, MMF, 300m, DOM):


ATGBICS X4455AXFP 10GBase-SR supports a distance of up to 300m over multi mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Sun Oracle X4455A= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *	Fiber optic 10000 Mbit/s	Certification	CE, FCC, RoHS
Maximum data transfer rate *10000 Mbit/sInterface type *XFPSingle-mode fiber (SMF) supportedXMulti-mode fiber (MMF) supportedImage: Compare transfer		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1.5 W
SFP transceiver standard	SR	Operational conditions	
Maximum transfer distance 300 m Wavelength 850 nm Ethernet LAN ✓ Ethernet interface type 10 Gigabit Ethernet Digital Diagnostics Monitoring (DDM) ✓	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95%	
	✓	Storage relative humidity (H-H) Weight & dimensions	0 - 95%
Wavelength-division multiplexing (WDM)	×	Width	18.5 mm
Features		Depth	71 mm
Product colour Housing material	erial Metal	Height Weight	8.5 mm 36 g
Plug and Play		Packaging data	
Hot-Plug support Hot-swap	4	Number of products included Package type	l pc(s) Box
Easy to install	1	Technical details	
Country of origin Brand compatibility	United Kingdom Oracle	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead

Product code: X4455A-C



5056468712530

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.