

## Coaxial Cable Connector 11\_N-50-7-69/133\_N

### Description

Straight cable plug

SUHNER full crimp cable attachment

Ingress protection according to IP67



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$		
Interface frequency max.	11 GHz		
Frequency range	DC to 2 GHz	2 to 4 GHz	4 to 6 GHz
Return loss	$\geq 30$ dB	$\geq 23.8$ dB	$\geq 23$ dB

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0345 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	

### Related Documents

Outline drawing	DOU-00008098
Catalogue drawing	DCA-00245537
Assembly instruction	DOC-0000311731

### Ordering Information

Single package	11_N-50-7-69/133_NE
Bulk 100 pcs package	11_N-50-7-69/133_NH

### Additional Information

Suitable cables	SPUMA_400, SPUMA_400-FR-01, Spuma_400-RS-FR, LMR-400
Interface standards	IEC 61169-16_MIL-STD-348A/304_CECC 22210