

Between Series Adaptor 32_4310-716-50-X2/133_W

Description

PIM Adaptor plug/plug
4.3-10 plug (male) / 7/16 plug (male)

Interface standards
Series 4.3-10 - IEC 61169-54
Series 7/16 - IEC 61169-4_CECC 22190_DIN 47223_VG 95250

Benefits

Low passive intermodulation (PIM) adaptor



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 7.5 GHz

PIM, 3rd order intermodulation distortion (IMD) max. Static -155 dBc at 2x 43 dBm / 20 W carrier

Mechanical Data

Number of matings 500
Weight 0.117 kg

Environmental Data

Operating temperature -55 °C to 90 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Interface - 4.3-10 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - 7/16 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00287206

Ordering Information

Single package 32_4310-716-50-X2/133_WE

Remarks

PIM typ. -166 dBc at 2 x 20 W / 43 dBm

Between Series Adaptor 32_4310-716-50-X2/133_W