


THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

J

COMPLIANT





| Ν | 0 | TE | ΞS | S: | |
|---|---|----|----|----|--|
| | | | | | |

| MATERIAL: HOUSING: SHELL: CONTACT: | THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED |
|---|---|
| OPERATING TEMPERATURE: | -55°C ~ 125°C |
| POWER/CO-AX CONTACT RATING: (IF PRESENT) | 10A (CURRENT) |
| SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE: | |
| INSULATOR RESISTANCE: DIELECTRIC | 5000MΩ min. |
| WITHSTANDING VOLTAGE: | 1000V AC rms |

| | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | | |
|--------------------------------------|--|--------------------------|------------|-------|--|
| COMBINATION | DRAWN: C.B | DATE: JAN. 01/2019 | | | |
| | CHECKED: | DATE: | | | |
| EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| TORONTO, ONTARIO CANADA | | DRAWING NUMBER: 630-2W2- | 650-1N6 | ISSUE | |
| YOUR CONNECTION TO QUALITY & SERVICE | | PART NUMBER: 630-2W2- | 650-1N6 | 1 | |

