т 	۵	н п	m	C		0	Ξ			7
	Z	ØS								
						LAYOUT SHO	WN AS EXAMPLE			
		Keying Shov	vn as example							
CHARACTERISTICS			Connector dimension							
-Standard : Based on I	MIL-DTL-38999 Series III		Dim Nominal							
-Shell Material -Shell Plating -Insulator -Contacts	Shell Material: AluminiumØS25 MaxShell Plating: Olive drab CadmiumZ31 MaxShell Plating: Olive drab CadmiumVV THREADM15x1-6gInsulator: Thermoplastic: Thermoplastic				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Grommet -Contact Plating	: Silicon Elastomer : Gold over copper Alloy 0.8µm minir	mum					Country Jurisdi FR	iction & Control List Not Listed]	
-Durability -Delivered without So	: 500 Mating cycles					PN: 8D5	511W05SDL			
-Temperature Range				Г						_
-Salt Spray	: 500 hours				A 17-10-2016	FIrst Release				
– -Mass	: 16.04 g ± 10%			-	ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	-
			TITLE	Aluminium Plug 8D series						
BASIC SERIES:	8D 5 - 11	1 W 05 S D	L	_	SCALE	Genera	I linear	NPRDS / PROJECT		_
SHELL TYPE : Plug wi				W/O Contacts	NA		ances:	859		
CONTACT TYPE : Sta								This document is the prop SOURIAU	perty of	_
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)				SOURIAU WWW.SOURIAU.COM it must not be reproduce communicated without perr						
	Olive drab Cadmium		CONTACT	AYOUT : 11-05	FORMAT	SOU	RIAU DRG N°		SHEET	_
PLATING : W =					A3					

_	Ŧ	۵	וד	m		0
		Contact Layout				
4	- <u>x</u> _	$ \begin{array}{c} & & \\ & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & $				
	Conta positio ID A B C C D E Shell Arrangement Numb size no.	X-axis (mm) Y-axis (mm) +0.65 (1.65) +0.65 (1.42) +.113 (2.87) 065 (1.65) +.000 (0.00) 130 (3.30) 113 (2.87) 065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) 065 (1.42)				
ω	11 -5 5	20 I All MS20050-5				
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
0						Count FR
					A 17-10-20 ISS DATE Designed By:	PN: 8D511V 16 First Release Latest modification - by Date:
					TITLE	Alumir General linear
<u> </u>					NA	Tolerances:
					FORMAT A3	SOURIAU 8D511W
L	Н	G	F	E	D	C

	σ			А			
		I					
						4	
						3	
anv n	ion-conformit	v or dam	age				
whic	h does not co ne Parties or b	mply wit	h				
	n, technical n		μαιτγ				
ntry	Jurisd	liction &	Control L	ist]		
R		Not Lis]	2	
W)5SDL						
					MOD N°		
		CUSTO	MER DR	AWING			
inium Plug 8D series							
n NPRDS / PROJECT							
		Th	859	nt is the pro	perty of	1	
.CO	M						
		be reproduc d without pe	rmission				
	DRG N°				SHEET		
VUS	5SDL-C			A	2/2	J	
	В	I		А			