


## 4-outlet Vertical Power Strip with 6-ft. Cord

MODEL NUMBER: PS240406









The PS240406 power strip provides horizontal or vertical power distribution for rackmount, raceway and workbench applications in a convenient 24-in. mountable housing.

#### Description

The PS240406 provides a 15-amp, 120v power strip with 4 standard NEMA 5-15R outlets in a rugged, all-metal, mountable housing. It allows for both vertical and horizontal mounting, making it ideal for a variety of uses including office, rackmount, workbench, industrial and telecom applications. With a NEMA 5-15P, 6-ft. power cord, you don't have to install the PS240406 next to outlets you already have; it can be mounted across the room and deliver reliable service where you need it most. A lighted and covered On/Off switch helps prevent accidental shut-offs, while a 15-amp circuit breaker guards against dangerous circuit overloads. Its sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

### **Features**

**Multi-Outlet Power Distribution** 

Vertical or Horizontal Moun

**Premium Safety Features** 

**Heavy-Duty Housing** 

# **Specifications**

OVERVIEW	
UPC Code	037332186614

### **Highlights**

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment
- 24-in. mountable housing with 4 standard NEMA 5-15R outlets and a 6-ft. power cord
- Lighted, covered On/Off switch and 15-amp circuit breaker
- Sturdy construction and heavyduty, all-metal housing

### **Package Includes**

- PS240406
- Mounting hardware
- Instruction manual



OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(4) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(4) Yes	
Outlet Spacing	5.67 in.	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.64 x 3.50 x 27.64	
Shipping Dimensions (hwd / cm)	6.71 x 8.89 x 70.21	
Shipping Weight (lbs.)	2.29	
Shipping Weight (kg)	1.04	
Unit Dimensions (hwd / in.)	24 x 1.5 x 1.5	
Unit Dimensions (hwd / cm)	61 x 3.8 x 3.8	
Unit Weight (lbs.)	1.65	
Unit Weight (kg)	0.75	
Material of Construction	Aluminum	
Included Mounting Accessories	Includes mounting clips	
Integrated Keyhole Mounting Slots	No	
Receptacle Color	Black	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

	<u></u>	
Color (AC Line Cord)	Black	
Color	Silver	
Form Factors Supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications	
Outlets Measurement (Center to Center)	5.67 in.	
Anti-Microbial Protected	No	
CERTIFICATIONS		
UL1363 (Power Tap)	UL1363	
Canada	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>