

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	08MAY2015	DW	CW
	B	ECR-15-013292	24SEP2015	DL	CW
	C	ECR-21-105887	26JUL2021	BS	CW
	D	ECR-22-150866	20SEP2022	DL	CW

4X M3 SCREW, RECOMMENDED TIGHTENING TORQUE 0.5Nm

M4 SCREW RECOMMENDED TIGHTENING TORQUE 1.2Nm

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250 V  
RATED CURRENT: 10 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4 KV  
POLLUTION DEGREE: 3  
CONTACT RESISTANCE:  $\leq 5 m\Omega$   
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20200X10XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 10A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4 KV  
污染等级: 3  
接触电阻:  $\leq 5 m\Omega$   
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
接线类型: 冷压接
- 端子需要单独订购。  
(订货号参考图面: T20200X10XX000)

PANEL CUT FOR INSERTS FOR USE WITHOUT HOODS/ HOUSINGS

4X  $\phi 3.3$

HDD-072-M 73-144	T2031442101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	08MAY2015	David Wang	
		CHK	08MAY2015	Chris Wang	
		APVD	08MAY2015	Xiang Xu	
		PRODUCT SPEC	108-137043		
		APPLICATION SPEC	114-137043		
		WEIGHT	-		
		Customer Drawing		SCALE	1:1
		SHEET		1 OF 1	REV D

HDD-072-M 73-144

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A300779 T2031442101000

1470-19 (3/13)