





LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

ယ

 \sim

-Mass

BASIC SERIES:

SHELL SIZE : 11

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : W = Olive drab Cadmium

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Aluminium				
-Shell Plating	: Olive drab Cadmium				
-Insulator	: Thermoplastic				
-Contacts	: Copper Alloy				
-Seals & Grommet	: Silicon Elastomer				
-Contact Plating	: Gold over copper Alloy $0.8 \mu m$ minimum				
-Durability	: 500 Mating cycles				
-Delivered without Souriau contacts					
-Temperature Range	_: -65°C to +175°C				
-Salt Spray	: 500 hours				

: 11.02 g ± 10%

8D 0

G

11

W

02

Ρ

F

E L

Connector dimension				
Dim	Nominal			
Р	3.25±0.2			
PP	4.93±0.2			
R1	20.62			
R2	18.26 26.2±0.3			
S				
V	20.83+0/-1.25			
W	2.1/2.5			
Z	31.5 Max			
VV THREAD	M15x1-6g			

Delivered W/O Contacts

CONTACT LAYOUT : 11-02

CONTACT TYPE : PIN(500 Matings)

Е

ORIENTATION : E

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend



Φ	Þ					
		4				
S EXAMPLE		3				
any non-conformit which does not co or of the Parties or b dation, technical no untry Jurisd R UWO2PEL	mply with by a third party	2				
	MOD N°					
um Receptacl	customer drawing m Receptacle 8D series					
ar	NPRDS / PROJECT 859					
I.COM	COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
U DRG N° N02PEL-C	SHEET 1/2					
В	A					

r	Ξ	G	т –	m	D	0
		Contact Layout				Panel Cuto
4	-x (1	+Y +B B A +X 095 -Y (2.4imm)				SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
	po	Contacts (Insert arrangement 11-2) ntact Contact location sition D X-axis (mm) Y-axis (mm) A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00) t Number of contacts Size contacts Service rating loca Contacts 2 16 I A	tact tion JI			
ω						Dim ØA ØAA R1 ØT
	F					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						PN: 8D011V
					A 07-10-201 ISS DATE Designed By:	Latest modification - by Date:
-					SCALE NA	Aluminiur General linear Tolerances: ±
					FORMAT A3	WWW.SOURIAU.C SOURIAU 8D011W
L	Н	G	F	E	D	C

