	T G T	m		C	œ	A		
4	R 22.6 Max (true) (true) (true	S C C C C C C C C C C C C C C C C C C C			AS EXAMPLE			4
	Keyin	g Shown as example						
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimensionDimNominalA38.1±0.3						
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g		SOURIAU shall not be liable f due to a use of the Produ the Specifications issued by eit (professional recomm	cts which does not compl	y with third party		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum					on & Control List ot Listed		2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D71	.3W26SCL			
	-Temperature Range _: -65°C to +175°C -Salt Spray : 500 hours	A 29-09-2016	A 29-09-2016 First Release					
	-Mass : 25.84 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CL	JSTOMER DRAWING	MOD N°	
		TITLE	TITLE Aluminium Receptacle 8D series					
	BASIC SERIES: 8D 7 - 13 W 26 S	C L Delivered W/O Conta	SCALE	General lin Toleranc		NPRDS / PROJECT 859		
<u> </u>	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact		NA ± 859 SOURIAU WWW.SOURIAU.COM This document is the property SOURIAU it must not be reproduced on				_ 1	
	SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings) PLATING : N/L = Olive drab Cadmium CONTACT LAYOUT : 13 26			communicated without permis				
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-	A3		AU DRG N° 3W26SCL-C		1/2	
L	H G F	E	D	С	В	A		_

ſ	Т	Q	П	п		
4	Contact Layout 26 PRESS 2#12				Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4
ω.	Ctc A B C D E F 1 2	6#22D 13-26 X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 -4.34 3.25 0 -3.25 0			Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0	3
2					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	2
_					ISS DATE Latest modification - by MOD N Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series SCALE General linear NA Tolerances: ± 859 SOURIAU WWW.SOURIAU.COM FORMAT SOURIAU A3 SOURIAU DRG N°	1