



注記 NOTES

1. 各部の反りは0.5最大。
WARPING : 0.5 MAX.
2. サークットNO.はNO."1"のみ表示。
CIRCUIT NO. : 1 ONLY.

24.9	19.8	39-01-1065	5195-063	6
20.94	15.84	39-01-1055	5195-053	5
13.02	7.92	39-01-1035	5195-033	3
9.06	3.96	39-01-1025	5195-023	2
B	A	EDP NO.	MATERIAL NO.	極数 NO. OF CKTS.
			MODEL NO.	5195-N3

サーキットNO. CIRCUIT NO. ENG. NO. トレードマーク TRADE MARK

REVISED EC NO: J2009-0049 DRWN: MAKURAA 2008/07/23 CHKD: T. HARIYAMA 2008/07/23 APPR: NUKITA 2008/11/14 G	DESCRIPTION GENERAL TOLERANCES (UNLESS SPECIFIED) 10 UNDER ±0.2 10 OVER 30 UNDER ±0.25 30 OVER ±0.3 ANGULAR ±3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE MM ONLY	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		DRAWN BY T. ASAKAWA DATE '95/5/9		TITLE SPOX 3.96 PITCH RECEPTACLE HOUSING			
		CHECKED BY S. A DATE '95/5/9		APPROVED BY M. FUKUSHIMA DATE '95/5/9		MOLEX MOLEX INCORPORATED	
		MATERIAL NO.		SEE TABLE		DOCUMENT NO. SD-5195-002	SHEET NO. 1 OF 1

材料 MATERIAL
ナイロン66, UL94V-0
NYLON66, UL94V-0