		m		0			
CHARCTERISICS Shell Nativity: Stand or U: Stand o							
Standard : Based on MIL DTL 38999 Series III III IIII IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Keying Sho			LAYOUTS	HOWN AS EXAMPLE		
- Ourability ::::::::::::::::::::::::::::::::::::	-Shell Material: Composite-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	Dim Nominal ØS 41.7 Max Z' 31.5 Max		due to a use of the the Specifications issued	Products which does not com d by either of the Parties or by commendation, technical not Country Jurisdict	oly with a third party ice.) tion & Control List	
-Mass : 50.4 g ± 10% -Mass : 50.4 g ± 10% BASIC SERIES: 8D 5 - 21 M 16 S C SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 PLATING : M = Nickel - Mass : 50.4 g ± 10% - MOD N° - MOD	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C		A 07-10-2016				
BASIC SERIES: 8D 5 - 21 M 16 S C SCALE SCALE SCALE NPRDS / PROJECT 859 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : C NA SOURIAU SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 21-16 FORMAT SOURIAU DRG N° SHEET						CUSTOMER DRAWING	MOD N°
BASIC SERIES. BD SD <td></td> <td></td> <td>TITLE</td> <td></td> <td>Composite Plug 8D</td> <td>series</td> <td></td>			TITLE		Composite Plug 8D	series	
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) PLATING : M = Nickel CONTACT LAYOUT : 21-16 FORMAT SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU WWW.SOURIAU.COM SOURIAU WWW.SOURIAU.COM					olerances:	859	erty of
			SOURIAU	SOURIAU WWW.SOURIAU.COW it must not be reproduced or			
	PLATING : M = Nickel	CONTACT LAYOUT : 21-16					

r	т	۵	г	m	U	0	
		Contact Layout					
4		$-X \left(\begin{array}{c} \bullet & \bullet^{*Y} \\ \bullet & \bullet \\ \bullet \\$					
	Contract X-axis position ID X-axis A +.118 (3.00) B +.271 (6.88) C +.341 (8.66) D +.308 (7.82) E +.162 (4.62) F +.000 (0.00)	Contacts (insert arrangement 21-16) vation Contact position Location Y-axis D -X-axis Y-axis + .322 (8.18) J 341 (8.66) +.036 (0.91) + .211 (5.36) K 271 (6.88) +.211 (5.36) + .036 (0.91) L 118 (3.00) +.322 (8.18) 150 (3.81) M +.000 (0.00) +.175 (4.45) 290 (7.37) N +.154 (3.91) +.062 (1.57) 343 (8.71) P +.094 (2.39) 122 (3.10)					
ω	G 182 (4.62) H 308 (7.82) Shell Arrangement NL size no. c 21 -16 c	343 (8.71) P +.094 (2.39) 122 (3.10) 290 (7.37) R 094 (2.39) 122 (3.10) 150 (3.81) S 154 (3.91) +.062 (1.57) umber of contacts Size Contact Supersedes 16 16 II All MS20055-16					
	-					SOURIAU shall not be liab due to a use of the Pro	ducts w
N						the Specifications issued by (professional recon	
					A 07-10-20	PN: 8D	521
					ISS DATE Designed By: TITLE	Date:	Comp
_ _					SCALE NA	Genera 	
					FORMAT	U WWW.SOUR SOU	
l	Н	G	F	E	A3	8D5	
					V		

