


REVISIONS												
REV	ECO	DESCRIPTION	DATE	BY	APPR							
A1	-	RELEASED	11NOV2020	J. HEAD	DH							



NOTES: UNLESS OTHERWISE SPECIFIED

1. PLUG MATERIAL:


SHELL: ZINC ALLOY, NICKEL PLATED COUPLING RING: ALUMINUM ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. BACKSHELL MATERIAL:


SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
- 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
- 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC PLUG DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
 - 6.3 MATING PART(S).
 - 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.







	AUDINIO0-7	HL98-24-169R-059								
	PART NUMBER			DESCRIPTION				ITEM		
QUANTITY		MATERIALS LIST								
	UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm).		SIGNATURES D		Amphonol					
Tolerances are a PL DEC ±0.30		DRAWN: J. HEAD 11NOV2020			Amphenol					
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.com					
3) Note reference	PROCESS SPECIFICATIONS: SPECIFICATION ONLY. DES SPECIFICATIONS AND PEI SHOWN HEREON ARE THIT THE AMPHENOL CORPOR OF REPRODUCTION ARE:		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036					
MATERIAL SPECIEICA				Clinton Township, Wi 46036				0		
MATERIAL OF EON ION			CUSTOMER:			DURAMATE AHDM PLUG, SIZE 24, WD THD,				
			THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SI IMPLECT TO NORMAL		KIT W/ CABLE CLAMP BACKSHELL					
					B	C-	AHDM06-24-16		A1	
NEXT ASS'Y:			RING VARIATION	ONS.	SCALE: N	ONE	SH	HEET 1 OF	1	

AUDMOS 24 16CD OFO

KIT,PLUG AND BACKSHELL,SZ 24 DWG NO: AHDM06-24-16SR-059

REV: A1 SH: