

ATGBICS CAB-OM4-LC-ST-1M-S fibre optic cable LC/UPC ST/UPC OFNR Aqua colour

Brand: ATGBICS **Product code**: CAB-OM4-LC-ST-1M-S

Product name: CAB-OM4-LC-ST-1M-S

LC-ST OM4 Fibre Optic Cable Multimode Simplex Aqua 1m

ATGBICS CAB-OM4-LC-ST-1M-S fibre optic cable LC/UPC ST/UPC OFNR Aqua colour:

This product is high quality Simplex LC-ST (male to male) Fibre Patch Cable. Simplex Fibre is most often used for applications that only require one-way data transfer. The OM4 cable type has a higher attenuation that helps reduce losses over greater distances. The OM4 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns.

ATGBICS CAB-OM4-LC-ST-1M-S. Cable length: $\vec{1}$ m, Cable type: OFNR, Fibre optic type: OM4, Connector 1: LC/UPC, Connector 2: ST/UPC, Core diameter: $50~\mu m$





Features		Features	
Cable length * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Cable type * Fibre optic type *	Dennector 1 * LC/UPC Dennector 2 * ST/UPC Dennector 1 gender * Male Dennector 2 gender * Male Dennector 3 gender * Dennector 3 gender Dennector 3 gender * Male Dennector 4 Male Dennector 3 gender * Dennector 4 gender Dennector 4 gender * Male Dennector 3 gender * Male Dennector 4 gender * Male Dennector 4 gender * Male Dennector 2 gender * Male Dennector 3 gender * Male Dennector 3 gender * Male Dennector 4 gender * Male Dennector 3 gender * Male Dennector 4 gender * Male Dennector 4 gender * Male Dennector 5 gender * Male Dennector 5 gender * Male Dennector 6 gender * Male Dennector 6 gender * Male Dennector 7 gender * Male Dennector 9 gender * Dennector 9 gen	Insertion loss Return loss Jacket material * Country of origin Technical details Sustainability certificates	0.2 dB 50 dB Polyvinyl chloride (PVC) China
Product colour * Full duplex Core diameter Cladding diameter		Operational conditions Operating temperature (T-T) Storage temperature (T-T)	Halogen -40 - 70 °C -40 - 70 °C
Fiber mode structure Wavelengths supported Ethernet interface type		Weight & dimensions Cable diameter Packaging data Quantity per pack	3 mm



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.