
THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER

ORIGINAL

1





MATERIALS:

. HOUSING: PBT, UL94V-0, BLACK COLOR

2. INSULATOR: PBT, UL94V-0, WHITE COLOR

3. WIRE-HOUSING SEAL: SILICON RUBBER

SPECIFICATIONS

1. PITCH: 2.5MM

RATED VOLTAGE: 250V

3. RATED CURRENT: 3A MAX

. WITHSTAND VOLTAGE: AC1000V R.M.S.

5. CONTACT RESISTANCE: 15 mOHMS MAX


6. INSULATION RESISTANCE:


1000 MOHMS MIN/DC 500V

7. TEMPERATURE RANGE: -40° C ~ $+105^{\circ}$ C

B. WATERPROOF GRADE: TESTED AND

CERTIFIED TO IP67





ITEM NO.	DESCRIPTION	QTY.
1	565-005-000-410_Housing	1
2	565-005-000-410_Rear Insulator	1
3	565-005-000-410_Rear Gasket	1

Waterproof Connector, Insulator, Female, Black, 5Pin (22-28AWG) 565-005-000-410

EDAC INC

TORONTO, ONTARIO

CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC. AND
SHALL NOT BE REPRODUCED,OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

 ACAD REFERENCE NO.
 565-005-000-410

 DRAWN:R.STA.MONICA
 DATE: OCT.22/10

 CHECKED:
 DATE:

 SCALE:
 NOTTO SCALE
 SHEET 1 OF 1

ISSUE

565-005-000-410



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY