ב בר	т   т	D	)	0	ω			7
4								4
				LAYOUT SHOW	N AS EXAMPLE			3
	Koving Chown og overnele							
CHARACTERISTICS	Keying Shown as example							
-Standard : Based on MIL-DTL-38999 Series III	Connector dir Dim	mension Nominal						
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS Z VV THREAD	35.7 Max 31 Max M25x1-6g		SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomm	ucts which does not comp	ly with third party		
-Seals & Grommet : Silicon Elastomer						on & Control List Iot Listed		2
<ul> <li>Contact Plating : Gold over copper Alloy 0.8μm minimum</li> <li>Durability : 500 Mating cycles</li> <li>Delivered without Souriau contacts</li> </ul>				PN: 8D5	17F06SDL			4
-Temperature Range : -65°C to +200°C		Γ	A 14-10-201	L6 First Release				_
-Salt Spray : 48 hours			ISS DATE	Latest modification - by			MOD N°	_
			Designed By:	Date:		CUSTOMER DRAWING	MODIN	
			TITLE Aluminium Plug 8D series			series		
→ BASIC SERIES: 8D 5 - 17 F SHELL TYPE : Plug with RFI Shielding	06 S D L	Delivered W/O Contacts	SCALE	General I Toleran ±	ces:	NPRDS / PROJECT 859		_
CONTACT TYPE : Standard Crimp Contact		ORIENTATION : D	SOURIAL	J WWW.SOURIA	AU.COM	This document is the prop SOURIAU it must not be reproduce	ed or	_
SHELL SIZE : 17	L	TYPE : SOCKET(500 Matings)	FORMAT			communicated without per	rmission SHEET	
PLATING : F = Nickel		CONTACT LAYOUT : 17-06	A3		IAU DRG N°			
			AJ I	VI151	.7F06SDL-C		1/2	

r	Ŧ	۵	<del>ات</del>	m		0	
		Contact Layout					
4	-x (	$ \begin{array}{c} \bullet^{+Y} \\ \bullet \\ $					
	Conta	Contacts (Insert arrangement 17-6) act Location					
ω	A B C D E F Shell Arrangement Nun	(mm)         (mm)           +.121 (3.07)         +.209 (5.31)           +.241 (6.12)         +.000 (0.00)           +.000 (0.00)        241 (6.12)          241 (6.12)         +.000 (0.00)          121 (3.07)         +.209 (5.31)           +.000 (0.00)        000 (0.00)	1				
	<u>size no. co</u> 17 -6	ntacts contacts rating location 6 12 I All MS20053-6					
N						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts wl y either o
10						PN: 8D	
					A 14-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:	
_					SCALE NA	General General Toler	Alumir al linear rances: ±
					SOURIA		
					FORMAT A3		RIAU
	Н	G	F	E	D	C	

