ш Д Д			0	Β	A	
Z T T T T T T T T T T T T T T T T T T T						
			LAYOUT SHOWN AS E	XAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
<ul> <li>-Standard : Based on MIL-DTL-38999 Series III</li> <li>-Shell Material : Aluminium</li> <li>-Shell Plating : Black Zinc Nickel</li> <li>-Insulator : Thermoplastic</li> <li>-Contacts : Copper Alloy</li> <li>-Seals &amp; Grommet : Silicon Elastomer</li> <li>-Contact Plating : Gold over copper Alloy 0.8µm minimum</li> </ul>	DimNominalØS35.7 MaxZ31 MaxVV THREADM25x1-6g		SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either o (professional recommendat	hich does not comply wit f the Parties or by a third tion, technical notice.)	n party Control List	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D517Z	206SCL		
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 18-10-2016	5 First Release			
Mass : 29.9 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTC	MOD I	N°
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES:     8D     5     -     17     Z     C       SHELL TYPE     : Plug with RFI Shielding     -     17     Z     C	06 S C L Delivered W/O Cor	scale ntacts NA	General linear Tolerances: ±		DS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17	ORIENTATIO CONTACT TYPE : SOCKET(500 Ma		SOURIAU         This document is the property of SOURIAU           it must not be reproduced or communicated without permission			
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT :		SOURIAU	DRG N°	SHEET	
<b>_</b>			8D517Z0		1/2	

r	Ŧ	G	гт —	m	Ū	0
		Contact Layout				
4		+Y				
	-x -	$ \stackrel{\mathbb{E}}{\longrightarrow} \stackrel{\mathbb{A}}{\oplus} $ $ \stackrel{\mathbb{P}}{\oplus} \stackrel{\mathbb{E}}{\oplus} \stackrel{\mathbb{B}}{\oplus} $				
		C⊕ €Y				
	Conta	Contacts           (Insert arrangement 17-6)           act         Location           X-axis         Y-axis           (mm)         (mm)				
	A B C D E	+.121 (3.07) +.209 (5.31) +.241 (6.12) +.000 (0.00) +.000 (0.00)241 (6.12) 241 (6.12) +.000 (0.00)				
ယ	Shell Arrangement Nur size no. co					
	-					SOURIAU shall not be liable for a
						due to a use of the Products w the Specifications issued by either (professional recommenda
N						Count
						PN: 8D517
					A 18-10-20	016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumi
<b>_</b>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAL 8D517Z
L	Н	G	F	E	D	C

	œ			A		
						4
						3
whic r of t datio ntry	non-conformit h does not co he Parties or k n, technical n Jurisd	mply without a third otice.)	th d party Control List			
R Not Listed 7Z06SCL						2
		CUST			/IOD N°	
customer drawing						
	NPRDS / PROJECT 859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						1
	DRG N° SSCL-C				SHEET 2/2	
_00	B			A	-	