т   G "	<b>—</b>		0			
Keying Sh	nown as example		LAYOUT SHO	OWN AS EXAMPLE		
-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Composite-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	Connector dimensionDimNominalØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Contact Plating   : Gold over copper Alloy 0.8μm minimum     -Durability   : 500 Mating cycles     -Delivered with Souriau contacts and Accessories     -Temperature Range   : -65°C to +200°C		A 08-10-2016		FR N 0521M48SB	ot Listed	
-Salt Spray : 2000 hours - Mass : 62.4 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	C	USTOMER DRAWING	MOD N°
		TITLE Composite Plug 8D series				
BASIC SERIES: 8D 5 - 21 M 48 S   SHELL TYPE : Plug with RFI Shielding	В	SCALE NA	-{	ral linear rances: ±	NPRDS / PROJECT 859	
CONTACT TYPE   : Standard Crimp Contact     SHELL SIZE   : 21	ORIENTATION : B CONTACT TYPE : SOCKET(500 Matings)			d or		
PLATING : M = Nickel	CONTACT LAYOUT : 21-48	FORMAT A3		IRIAU DRG N° 521M48SB-C		SHEET 1/2
H G F	E	D	C	В	A	

	т	۵	н <b>г</b>	m	D	0	
		Contact Layout					
4	-*						

F

Е

G

Н

4#8 Power

21-48					
x	Y				
4.57	4.57				
4.57	-4.57				
-4.57	-4.57				
-4.57	4.57				
	X 4.57 4.57 -4.57				

ယ

 $\sim$ 

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country FR PN: 8D521M48SB 08-10-2016 First Release А DATE Latest modification - by ISS Designed By: Date: TITLE SCALE General linear  $( \bigcirc$ Tolerances: NA ±---**SOURIAU** WWW.SOURIAU.COM FORMAT A3 С D

