

## NOTES: UNLESS OTHERWISE SPECIFIED

## 1. PLUG MATERIAL:


SHELL: ZINC ALLOY, NICKEL PLATED COUPLING RING: ALLUMINUM ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER

## 2. BACKSHELL MATERIAL:


SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

#### 3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25℃.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
- 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
- 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC PLUG DRAWING FOR:
  - 6.1 CONTACT SIZE AND WIRE RANGE.
  - 6.2 RETAINING RING COLOR.
  - 6.3 MATING PART(S).
  - 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.







	AHDM06-2	AHDM06-24-18PR-059		HD36-24-18PE-059				
	PART NUMBER			DESCRIPTION				ITEM
QUANTITY		MA	TI	ERI	٩LS	S LI	ST	
	WISE SPECIFIED	SIGNATURES		DATE	1 mahanal		1	
All dimensions a     Tolerances are a     PL DEC +0.30		DRAWN: J. HEAD 16MAR202		16MAR2020	Amphenol			
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.com			
3) Note reference	Note reference = X ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
APPROVAL:		APPROVAL:					Clinton Township, Wi 40030	
		CUSTOMER:			DUI		ΓE AHDM PLUG, SIZE 24, W	
		THIS DRAWING IS SUPPLINFORMATION ONLY DES				KIT W	// CABLE CLAMP BACKSHE	LL
PROCESS SPECIFICATIONS:		SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		B	C-	AHDM06-24-18PR-059	A1	
NEXT ASSY: MANUFACTURING VARIATION		TIONS		SCALE: N	ONE	SHEET 1	of <b>1</b>	

DWG NO: AHDM06-24-18PR-059

KIT,PLUG AND BACKSHELL,SZ 24

9 REV: A1 SH: 1

1 SH: 1 OI

# **AT Series™** - Contact Size 16 Options

Machined Contacts, Sockets & Pins							
Part Number Description			AWG	Туре			
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined			
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined			
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined			
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined			
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined			
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined			
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined			
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined			
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined			
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined			
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined			
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined			

Tooling - Machined Contacts					
Part	Part Number	Description			
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)			
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)			

Contact Removal Tools					
Part	Part Number	Description			
3	ATRT-100	Used for removal of contacts for A Series™ products			
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16			
	A114017	Sealing Plug, Size 16, White			

Stamped & Formed Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Type	
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed	
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed	
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed	
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed	
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed	
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed	
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed	
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed	
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed	
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed	
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed	
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed	
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed	
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed	
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed	
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed	

	Tooling - Stamped & Formed Contacts						
Part	Part Number	Description					
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)					
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)					
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)					
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)					
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)					
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)					
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)					

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

# MagnaMate™ ATHP - DuraMate™ AHDP - DuraMate™ AHDM Series - Contact Size 12 Options

Machined Contacts, Sockets & Pins						
Part Number Description Size AWG						
AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined		
AT62-203-12141-10	Female Contact - Socket, Nickel-plated	12	10-12	Machined		
AT60-220-1231	Male Contact - Pin, Gold-plated	12	12-14	Machined		
AT62-210-1231	Female Contact - Socket, Gold-plated	12	12-14	Machined		
AT60-204-12141	Male Contact - Pin, Nickel-plated	12	12-14	Machined		
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined		

DiagnosticGrade™ Machined Contacts, Sockets & Pins  • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective						
Part Number Description Size AWG Type						
65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined		
AT62-210-1231-1820	Female Contact - DiagnosticGrade™, Socket, Gold-plated	12	20	Machined		

Tooling - Machined Contacts				
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
33	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

Contact Removal Tools					
Part	Part Number	Description			
	AT11-337-1205	Contact Removal Tool, Plastic, Size 12			
	A114017	Sealing Plug, Size 12, White			

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed		
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed		
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed		
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed		
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed		
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed		
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed		
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number	Description			
	MFX-3973	Crimp Die - Size 12 (S&F contacts only)			
	MFX-3985	Crimp Die - Size 12 (S&F contacts only) 10-12AWG -02XX Series			
	ATT-12-00	Hand Crimp Tool - Size 12, 12AWG (S&F contacts only)			
	ATT-12-01	Hand Crimp Tool - Size 12, 10AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 01/2022

# **DuraMate™ ATHD Series™** - Contact Size 8 Options

Machined Contacts, Pins and Sockets						
Part Number	Description	Size	AWG	Туре	Amps	
AT60-204-08141	Male Contact - Pin, Copper Alloy, Nickel-Plated	8	8-10	Machined	60A	
AT62-203-08141	Female Contact - Socket, Copper Alloy, Nickel-Plated	8	8-10	Machined	60A	

Tooling - Machined Contacts					
Part	Part Number	Description			
	WA23	Heavy Duty Pneumatic Crimp Tool -Uses Universal Positioner Part No. WA23-101DA and Crimp Locator MFX-3961			
	WA23-2	Die Assembly -for CA-5E12 Heavy Duty Pneumatic Crimp Tool, Size 8			
Variety by Barrier B	WA23-10	Contact Locator, Size 8			
NAM	96-978-22	Crimper and Dies -for Size 10mm²-185mm² Wires			

Contact Removal Tools					
Part	Part Number	Description			
	AT114008	Contact Removal Tool, Plastic, Size 8, 8-10AWG			