



.XXX ±0.05

| $^{\circ}$ | _ |    |
|------------|---|----|
| ¥          |   | OF |
|            |   |    |

ISSUE NUMBER RIGINAL (1)





## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

**OPERATING TEMPERATURE:** 


10A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX. 5000MΩ min.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:

|  |                                       | SW REFERENCE NO.: 629 COMBO ASSEMBLY   |                                 |                  |       |
|--|---------------------------------------|--|---------------------------------|------------------|-------|
|  |                                       |  | DRAWN: C.B                      | DATE: JAN. 01/20 | 19    |
|  |                                       |  | CHECKED:                        | DATE:            |       |
|  | EDAC INC                              | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND   | SCALE: (IN C.A.D. 1:1)          | SHEET 1 OF       | 2     |
|  | EDACINC<br>TORONTO, ONTARIO<br>CANADA | SHALL NOT BE REPRODUCED.OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-3WK3240-1N2 |                  | ISSUE |
|  | YOUR CONNECTION TO QUALITY & SERVICE  |  | PART NUMBER: 629-3WK            | 3240-1N2         | 1     |

-55°C ~ 125°C

1000V AC rms





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

