







**ISSUE NUMBER** (1)





## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLAS STEEL, NICKEI COPPER ALLO		
OPERATING TEMPERATURE:	-55°C ~ 125°C		

ASTIC POLYESTER, UL94V-0 **KEL PLATED** LOY, 30µ GOLD PLATED


.XX ±0.13

.XXX ±0.05


30A (CURRENT) **POWER/CO-AX CONTACT RATING:** (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:





COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY				
		DRAWN: C.B		DATE: JAN. 01/2019		
		CHECKED:		DATE:		
EDAG INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE:	(IN C.A.D. 1:1)	SHEET 1 OF	2	
		DRAWING NUMBER: 630-13W3640-3NE		ISSUE		
		PART NU	MBER: 630-13W	3640-3NE	1	





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

