


.XX ±0.13

.XXX ±0.05




NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDANCE)	Σ
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	I
INSULATOR RESISTANCE:	5000MΩ min.	ا ک
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms	L

			SW REFERENCE NO.: 630 COMBO ASSEMBLY					
		DRAWN:	C.B	DATE:	JAN.	01/20	19	
		CHECKED):	DATE:				
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE:	(IN C.A.D. 1:1)	SHEET	1	OF	2
	TORONTO, ONTARIO CANADA OR USED AS THE BASIS FOR THE	DRAWING	NUMBER: 630-5W5-	-240-5T1			ISSUE	

PART NUMBER:



J COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	\sim	\mathbf{i}		
0À	N)		2	
Jan San		X	\rightarrow	
				\geq
	Y CO))	Ĭ
	N. N	s a	542	
		×.	K @	
			\sim	J

630-5W5-240-5T1

1

