	 			0	₩	A
CHARCTERSTICS Standard: Based on ML-DT-38999 Series III Shell Material ::::::::::::::::::::::::::::::::::::				LAYOUT SHOWN AS	EXAMPLE	
CHARACTERISTICS -standard: Based on MIL-DTL-38999 Series II -Shell Material : Composite -Shell Material : Composite -Shell Plating : Olive drab Cadmium -Insulator : Composite -Oracits : Composite -Oracits : Composite -Sociats : Composite -Sociats : Composite -Sociats : Composite -Sociats : Sociats -Diversed with Souriau contacts and Accessories : Sociats -Temperature Range : Sociats -Mass : 2.05 g i 10% -Mass : 2.05 g i 10% -Mass : 2.05 g i 10% -Stell_ttrpe: : Randard Crimp Contact -Stell_ttrpe: : Randard Crimp Contact -Stell_ttrpe: : Stell_stell -Stell_ttrpe: : Stel		Koving Shown as example				
BASIC SERIES: 8D 5 - 17 J 75 B D SHELL TYPE : Plug with RFI Shielding SCALE SCALE SCALE Tolerances: 859 NA 859 - 17 15 000000000000000000000000000000000000	-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Composite-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories-Temperature Range: -65°C to +175°C-Salt Spray: 2000 hours	Dim Nom ØS 35.7 Z' 31.5 VV THREAD M25x	Inal Max Max 1-6g A 14-10-201 ISS DATE	due to a use of the Products w the Specifications issued by either (professional recommends) Coun FR PN: 8D517	vhich does not comply with of the Parties or by a third party ation, technical notice.) try Jurisdiction & Contro Not Listed	 MOD N°
SHELL TYPE : Plug with RFI Shielding NA Step CONTACT TYPE : Standard Crimp Contact ORIENTATION : D SOURIAU SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) NA	BASIC SERIES: 8D 5 - 17	J 75 B D	SCALE	General linear	NPRDS / PF	
A3 8D517J75BD-C 1/2	CONTACT TYPE : Standard Crimp Contact		ORIENTATION : D DCKET(500 Matings) ACT LAYOUT : 17-75	J WWW.SOURIAU. SOURIAU	COM it must no communicat	nent is the property of SOURIAU ot be reproduced or ted without permission SHEET

	Ŧ	۵	וד	m	D	0
4		Contact Layout 75				
	Ctc A B	2#8 Triax 17-75 X Y 0 4.75 0 -4.75				
ω						
	-					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommendat
N						PN: 8D517.
					A 14-10-20 ISS DATE Designed By: TITLE	16 First Release Latest modification - by Date: Compo
-					SCALE NA SOURIAU	General linear Tolerances: ±
	Н	G	F	E	FORMAT A3 D	SOURIAU 8D517J7

